

MATERIAL SAFETY DATA SHEET

SECTION 1 – IDENTIFICATION

Product Name

ORANGE SQUEEZE

All Purpose Spray & Wipe Cleaner

Recommended Use

SupplierT/ACN :0Street Address1Telephone Number(0Facsimilie(0EmailtaWebsitewEmergency Telephone Number

TASMAN CHEMICALS PTY LTD 005 072 659 1-7 Bell Grove, Braeside , Victoria 3195 AUSTRALIA (03) 9587 6777 (03) 9587 5255 taschem@taschem.com.au www.tasmanchemicals.com.au r 1 800 334 556

SECTION 2 – HAZARDS INDENTIFICATION

Hazardous according to criteria of Safe Work Australia.

Hazard Catego	ory :	Xi	(Irritant)
<u>Risk Phrases</u> R36/38 R43			n and eyes sitisation by skin contact
<u>Safety Phrases</u> S2 S7 S24/25 S26	Keep o Keep c Avoid c	ontaine contact v	ach of children r tightly closed with skin and eyes act with eyes, rinse immediately with plenty of water and seek medical
S28 S37/39 S60 S61	Wear s This ma	uitable aterial a elease t	ith skin, wash immediately with plenty of water and seek medical advice gloves and eye/face protection nd its container must be disposed of as hazardous waste to the environment. Refer to special instructions/Material Safety Data

Orange Squeeze is not classified as a **Dangerous Good** according to the Australian Code for the Transport of Dangerous Goods by Road and Rail.

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	CAS Number	Proportion (%m/m)
Water	7732-18-5	Н
Anionic Surfactants Vegetable based	66585-34-2	Μ
Nonionic Surfactants Vegetable based	68515-73-1	Μ
Ethanol	64-17-5	L
Sodium Gluconate	527-07-1	L
Dye	Proprietary	L
D'Limonene VH>60% H>30-60% M=10-30% L=<10%	138-86-3	L

SECTION 4 – FIRST AID MEASURES

First Aid

Swallowed:	If swallowed <u>DO NOT</u> induce vomiting. Give a glass of water to drink. Seek immediate medical assistance or contact the Poisons Information Centre immediately.
Eye:	If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised by the Poisons Information Centre or a doctor, or for at least 15 minutes. Seek medical attention if effects persist.
Skin:	If skin or hair contact occurs, flush skin and hair with running water for 15 minutes
Inhaled	Remove victim from further exposure. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position. Seek medical attention if effects persist.
Advice to Doctor	

Treat symptomatically.

SECTION 5 – FIRE FIGHTING MEASURES

Fire/Explosion Hazard

This material is not combustible under normal conditions. However, it will breakdown under fire conditions and the organic component may burn. Not considered to be a significant fire risk. Fumes containing carbon dioxide, carbon monoxide and sulfur dioxide may be formed in large fires. Keep containers cool by spraying with water to prevent pressure building up inside the drums, causing them to burst.

Extinguishing Media

Use water spray, 'alcohol' foam, dry chemical or carbon dioxide. Avoid using large quantities of water.

SECTION 6 – ACCIDENTALRELEASE MEASURES

<u>Spills</u>

Slippery when spilled. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and/or eye contamination and the inhalation of mists or aerosols. Contain using sand or soil. Carefully dilute with water (fine spray or fog). Wash down area with excess water.

SECTION 7 – HANDLING AND STORAGE

Handling : Avoid skin and eye contact

<u>Storage</u>: Under normal weather conditions store in a well-ventilated area. Keep containers closed at all times when not in use. Check regularly for leaks. Remove drum bungs slowly to release any internal pressure.

SECTION 8 – EXPOSURE CONTROLS / PERSONALPROTECTION

Occupational Exposure Limits : Occupational Exposure Limits : Threshold Limit Values

Time Weighted Average (TWA)	=	1000 ppm (Ethanol)
Time Weighted Average (TWA)	=	80 ppm (D'Limonene)

Exposure Standards (TWA) is the time-Weighted average airborne concentration over an eight-hour working day, for a five day working week over an entire working life. According to current knowledge this concentration should neither impair the health or, cause undue discomfort to, nearly all workers.

<u>Engineering Control Measures</u> : Natural ventilation should be adequate under normal use conditions, Keep containers closed when not in use.

Personal Protective Equipment :

Eye: Safety glasses with side shields

Hands: Impervious plastic or rubber gloves.

Other: Not applicable

Respirator: Use with adequate ventilation.

Always wash hands before eating, drinking, smoking or using the toilet.

Wash contaminated clothing and other protective equipment before storage and reuse.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Odour: Melting Point:	Clear Irridiscent Orange Liquid	pH (as is): Flash Point:
Boiling Point:	100°C (approximately)	Volatiles
Density:@ 25°C Solubility:	1.01 grams/mL (approximately) Miscible	Flammable Limits: Perfume

8 to 10 Not applicable Water only Not applicable Orange Oil

SECTION 10 – STABILITY AND REACTIVITY

Stability Incompatible with strong oxidising agents

Reactivity

May react with strong oxidants.

SECTION 11 – TOXOLOGICAL INFORMATION

Health Effects

Acuto Effocte

No adverse health effects expected if the material is handled in accordance with the Material Safety Data Sheet. Symptoms that may arise if the material is mishandled are :

Acute Effects	
Swallowing:	This product is irritating to the gastro-intestinal tract. Ingestion may result in nausea, abdominal irritation, pain and vomiting.
Eye:	An eye irritant. Contamination of the eyes with may produce corneal damage
Skin:	Irritating to skin. On repeated or prolonged skin contact may lead to irritant contact dermatitis.
Inhaled:	The vapour or mist is irritating to mucous membranes and respiratory tract. Inhalation of the vapour may result in headache or nausea

Issue No 2 - ORANGE SQUEEZE	
Issue Date : 24/05/12	

Chronic Effects

Principal routes of exposure are by accidental skin and eye contact

SECTION 12 – ECOLOGICAL INFORMATION

Avoid contaminating waterways. Minor spills and residue may be hosed down with excess water to trade waste treatment plant Major spills should be contained, absorbed by sand or earth and placed in sealed plastic or epoxy-lined drums for disposal

SECTION 13 – DISPOSAL CONSIDERATIONS

Refer to Waste Management Authority . Normally suitable for disposal at approved land waste site

SECTION 14 – TRANSPORT INFORMATION

UN Number :

Subsidiary Risk :

Packing Group :

Not classified as a Dangerous Good by the Criteria of the Australian Dangerous Good Code

Not required

Not applicable

Not applicable

Proper Shipping Name :	
Dangerous Goods Class :	
Hazchem Code :	

SECTION 15 – REGULATORY INFORMATION

Classification Based upon information, classified as hazardous according to criteria of Safe Work Australia

Poisons Schedule Schedule 5

SECTION 16 – OTHER INFORMATION

Contact Points

<u>Organisation</u>	Location	<u>Telephone</u>	<u>Ask For</u>
Tasman Chemicals Pty Ltd	Braeside, Victoria, Australia	(03) 9587 6777	Technical Manager
Poisons Information Centre		13 1126	

MSDS are updated frequently. Please ensure that you have a current copy.

This MSDS summarises our best knowledge of the health and safety hazard information of the product; how to safely handle and use the product in the workplace. If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact Tasman Chemicals Pty Ltd. Our responsibility for products sold are subject to our standard terms and conditions, a copy of which appears on all invoices. It is also available on request. Where health or safety data given discloses a risk to the user or environment, it is the responsibility of the Purchaser to pass on that information to employees or those who may be using the product, ensuring that adequate safety procedures are used including good industrial hygiene.

Page 4 of 4 Prepared By : *Keith Sadlier*

Not applicable

Not applicable

Not applicable