

SAFETY DATA SHEET

Product Name DIVOFLOW HE

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Supplier name DIVERSEY AUSTRALIA PTY. LIMITED

Address 29 Chifley St, Smithfield, NSW, 2164, AUSTRALIA

Telephone (02) 9757 0300 **Fax** (02) 9725 5767

Emergency 1800 033 111 (24 hrs)

Email aucustserv@diversey.com

Web site http://www.diversey.com

Synonym(s) ALL PACK SIZES

Use(s) C.I.P. ALKALI FOR HEAT MODIFIED SOILS

SDS date 13 January 2015

2. HAZARDS IDENTIFICATION

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

Risk Phrases

R35 Causes severe burns.

R41 Risk of serious damage to eyes.

Safety Phrases

S1/2 Keep locked up and out of reach of children.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice

S37/39 Wear suitable gloves and eye/face protection.

S45 In case of accident or if you feel unwell seek medical advice immediately (show the label where

possible).

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

UN Number 1824 Transport Hazard Class 8
Packing Group II Hazchem Code 2R

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	CAS Number	EC Number	Content
SODIUM HYDROXIDE	1310-73-2	215-185-5	30%
NON HAZARDOUS INGREDIENTS	Not Available	Not Available	>60%

4. FIRST AID MEASURES

Eye If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until

advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.

Inhalation If inhaled, remove from contaminated area. To protect rescuer, use an Air-line respirator where an

inhalation risk exists. Apply artificial respiration if not breathing.

Skin If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running

water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.

Ingestion For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If

swallowed, do not induce vomiting.

ChemAlert.

Page 1 of 6

SDS Date: 13 Jan 2015

Product Name DIVOFLOW HE

Advice to doctor CORROSIVE POISONING TREATMENT: Immediate treatment preferably in a hospital is mandatory.

In treating corrosive poisoning, DO NOT INDUCE VOMITING; DO NOT ATTEMPT GASTRIC LAVAGE; and DO NOT ATTEMPT TO NEUTRALISE THE CORROSIVE SUBSTANCE. Vomiting will increase the severity of damage to the oesophagus as the corrosive substance will again come in contact with it. Attempting gastric lavage may result in perforating either the oesophagus or stomach. Immediately dilute the corrosive substance by having the patient drink milk or water. If the trachea has been damaged tracheostamy may be required. For oesophageal burns begin broad-spectrum antibiotics and corticosteroid therapy. Intravenous fluids will be required if oesophageal or gastric damage prevents ingestion of liquids. Long-range therapy will be directed toward preventing or

treating oesophageal scars and strictures.

Eye wash facilities and safety shower should be available. First aid facilities

5. FIRE FIGHTING MEASURES

Flammability Non flammable. May evolve toxic gases if strongly heated.

Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Fire and explosion

Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers

and nearby storage areas.

Extinguishing Use an extinguishing agent suitable for the surrounding fire.

Hazchem code 2R

> 2 Fine Water Spray.

R Wear liquid-tight chemical protective clothing and breathing apparatus. Dilute spill and

run-off.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS.

Prevent product from entering drains and waterways. **Environmental precautions**

Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, Methods of cleaning up

sand, or similar), collect and place in suitable containers for disposal.

References See Sections 8 and 13 for exposure controls and disposal.

7. STORAGE AND HANDLING

Store in a cool, dry, well ventilated area, removed from incompatible substances, heat or ignition Storage

sources and foodstuffs. Ensure containers are adequately labelled, protected from physical damage and sealed when not in use. Large storage areas should be bunded and have appropriate ventilation

Handling Before use carefully read the product label. Use of safe work practices are recommended to avoid

eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before

eating. Prohibit eating, drinking and smoking in contaminated areas.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure standards

Ingredient	Reference	TWA		STEL	
ingredient	Reference	ppm	mg/m³	ppm	mg/m³
Sodium hydroxide (peak limitation)	SWA (AUS)		2		

Biological limits No biological limit allocated.

Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical extraction **Engineering controls** ventilation is recommended. In a laboratory situation use under a fume cupboard or other localised

extraction ventilation equipment. Maintain vapour levels below the recommended exposure standard.



Page 2 of 6

SDS Date: 13 Jan 2015

Product Name DIVOFLOW HE

PPE

Eye / Face Wear splash-proof goggles. **Hands** Wear PVC or rubber gloves.

Body Wear coveralls. When using large quantities or where heavy contamination is likely, wear rubber

boots and a PVC apron. In a laboratory situation, wear a laboratory coat.

Respiratory Where an inhalation risk exists, wear a Type B (Inorganic gases and vapours) respirator.







9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance CLEAR TO SLIGHTLY HAZY AMBER LIQUID

Odour CHARACTERISTIC ODOUR

Flammability NON FLAMMABLE Flash point NOT RELEVANT **Boiling** point 100°C (Approximately) **Melting** point **NOT AVAILABLE Evaporation rate NOT AVAILABLE** Ηq > 13 (1% solution) Vapour density NOT AVAILABLE Specific gravity 1.335 - 1.355 Solubility (water) **MISCIBLE**

Vapour pressure **NOT AVAILABLE Upper explosion limit** NOT RELEVANT Lower explosion limit NOT RELEVANT Partition coefficient NOT AVAILABLE NOT AVAILABLE Autoignition temperature **Decomposition temperature** NOT AVAILABLE **Viscosity** NOT AVAILABLE NOT AVAILABLE **Explosive properties Oxidising properties** NOT AVAILABLE **NOT AVAILABLE** % Volatiles

10. STABILITY AND REACTIVITY

Chemical stability Stable under recommended conditions of storage. **Conditions to avoid** Avoid contact with incompatible substances.

Material to avoid Incompatible with oxidising agents (e.g. hypochlorites), acids (e.g. nitric acid) and metals.

Hazardous Decomposition

Products

May evolve toxic gases if heated to decomposition.

Hazardous Reactions Polymerization is not expected to occur.

11. TOXICOLOGICAL INFORMATION

Health Hazard

This product has the potential to cause serious adverse health effects. Use safe work practices to avoid eye or skin contact and inhalation. Over exposure may result in severe skin, eye and

respiratory burns with possible permanent tissue damage.

Eve Contact may result in irritation, lacrimation, pain, redness and corneal burns with possible permanent

eye damage.

Inhalation Over exposure may result in irritation of the nose and throat, coughing and bronchitis. High level

exposure may result in ulceration of the respiratory tract, lung tissue damage, chemical pneumonitis

and pulmonary oedema. Effects may be delayed.

Skin Contact may result in irritation, redness, pain, rash, dermatitis and possible burns. Effects may be

delayed.

Ingestion Ingestion may result in burns to the mouth and throat, nausea, vomiting, abdominal pain and

diarrhoea. Ingestion of large quantities may result in ulceration, unconsciousness, convulsions and



Page 3 of 6 SDS Date: 13 Jan 2015 **Product Name DIVOFLOW HE**

death.

SODIUM HYDROXIDE (1310-73-2) **Toxicity data**

> LD50 (intraperitoneal) 40 mg/kg (mouse) LDLo (ingestion) 500 mg/kg (rabbit)

12. ECOLOGICAL INFORMATION

Toxicity No information provided.

Persistence and degradability No information provided.

Bioaccumulative potential No information provided.

Mobility in soil No information provided.

Other adverse effects WATER: If released to waterways, alkaline products may change the pH of the waterway. Fish will

die if the pH reaches 10-11 (goldfish 10.9, bluegill 10.5). SOIL: May leach to groundwater with toxic effects on aquatic life as above. ATMOSPHERE: Not expected to reside in the atmosphere. Drops or

particles released to atmosphere should be removed by gravity and/or be rained out.

13. DISPOSAL CONSIDERATIONS

Waste disposal Neutralise with dilute acid (e.g. 3 mol/L hydrochloric acid) or similar. For small amounts, absorb with

sand or similar and dispose of to an approved landfill site. Contact the manufacturer/supplier for

additional information (if required).

Legislation Dispose of in accordance with relevant local legislation.

14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE



	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
UN Number	1824	1824	1824
Proper Shipping Name	SODIUM HYDROXIDE SOLUTION	SODIUM HYDROXIDE SOLUTION	SODIUM HYDROXIDE SOLUTION
Transport Hazard Class	8	8	8
Packing Group	II	II	II

Environmental hazards No information provided

Special precautions for user

Hazchem code 2R **GTEPG** 8A1 **EMS** F-A, S-B

15. REGULATORY INFORMATION

Classified as a Schedule 6 (S6) Standard for the Uniform Scheduling of Medicines and Poisons Poison schedule

(SUSMP).

Inventory Listing(s) **AUSTRALIA: AICS (Australian Inventory of Chemical Substances)**

All components are listed on AICS, or are exempt.



Page 4 of 6

SDS Date: 13 Jan 2015

16. OTHER INFORMATION

Additional information

EXPOSURE STANDARDS - TIME WEIGHTED AVERAGES: Exposure standards are established on the premise of an 8 hour work period of normal intensity, under normal climatic conditions and where a 16 hour break between shifts exists to enable the body to eliminate absorbed contaminants. In the following circumstances, exposure standards must be reduced: Strenuous work conditions; hot, humid climates; high altitude conditions; extended shifts (which increase the exposure period and shorten the period of recuperation).

WORKPLACE CONTROLS AND PRACTICES: Unless a less toxic chemical can be substituted for a hazardous substance, ENGINEERING CONTROLS are the most effective way of reducing exposure. The best protection is to enclose operations and/or provide local exhaust ventilation at the site of chemical release. Isolating operations can also reduce exposure. Using respirators or protective equipment is less effective than the controls mentioned above, but is sometimes necessary.

PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a ChemAlert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

Abbreviations

ACGIH Am	nerican Conference of Governmental Industrial Hy	gienists
----------	--	----------

CAS # Chemical Abstract Service number - used to uniquely identify chemical compounds

CNS Central Nervous System

EC No. EC No - European Community Number

GHS Globally Harmonized System

IARC International Agency for Research on Cancer

LC50 Lethal Concentration, 50% / Median Lethal Concentration

LD50 Lethal Dose, 50% / Median Lethal Dose

mg/m³ Milligrams per Cubic Metre
OEL Occupational Exposure Limit

pH relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly

alkaline).

ppm Parts Per Million

STEL Short-Term Exposure Limit

STOT-RE Specific target organ toxicity (repeated exposure)
STOT-SE Specific target organ toxicity (single exposure)

SUSMP Standard for the Uniform Scheduling of Medicines and Poisons

SWA Safe Work Australia
TLV Threshold Limit Value
TWA Time Weighted Average

Revision history

Revision	Description
1.1	Standard SDS Review
1.0	Initial SDS creation

Report status

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.



Page 5 of 6

SDS Date: 13 Jan 2015

Product Name DIVOFLOW HE

Prepared by

Risk Management Technologies 5 Ventnor Ave, West Perth Western Australia 6005 Phone: +61 8 9322 1711 Fax: +61 8 9322 1794 Email: info@rmt.com.au Web: www.rmt.com.au.

Revision: 1.1

SDS Date: 13 January 2015

End of SDS



Page 6 of 6

SDS Date: 13 Jan 2015