



## TRADESMATE SET

HARNESS / ADJUSTABLE LANYARD SET

### HLT17LX5

General purpose harness with front and rear D attachment points. Adjustable length lanyard with shock absorber and scaffold hook connected to rear dorsal. Full adjustable with quick connect buckles for ease of use. The adjustable lanyard is permanently attached so the wearer can easily work in fall restraint in many situations. Fall indicators for continued safety. Suitable for roofing, construction workers, vertical climbing, scaffolders, access equipment and general trades people.

**RATING:** 136kg


**LIFESPAN:** 10 Years

**CERTIFICATION:** EN 361:2002, EN 355:2002

EN 361:2002 Personal protective equipment against fall from a height. Full body harnesses

EN 355:2002 Personal protective equipment against falls from a height. Energy absorbers

CE 0082



MODEL	SIZE	WEIGHT (G)	DIMENSIONS	MATERIAL	RATING (KG)
HLT17LX5	UNI XXL	1460g 1600g	85 - 120cm waist 90 - 140cm waist	Polyester webbing 45mm Steel hardware	136kg

### PRODUCT FEATURES

- Versatile design allows use for a multitude of work applications.
- Polyester webbing construction for durability and strength.
- Quick connect buckles on leg straps and chest.
- Front and rear fall arrest D-ring attachment points.
- All forged steel hardware.
- An adjustable 2m lanyard is permanently attached to the back D-ring.
- Lanyard includes a scaffold hook.
- Effective means for ensuring the correct gear is worn correctly.

### ZERO HEIGHT SAFETY LIMITED

**AUSTRALASIA**  
10 Holt Place,  
Harewood, Christchurch 8053  
New Zealand  
sales.nz@zeroheightsafety.com

**EUROPE & UK**  
Badenerstrasse 122  
5466 Kaiserstuhl,  
Switzerland  
sales.eu@zeroheightsafety.com

zeroheightsafety.com

