# **RESPIRATORY GEAR**

# PROMESH® RESPIRATOR P2 WITH EXHALATION VALVE

**PRODUCT DATA SHEET: PC822** 



# PRODUCT CODE:







PRODUCT CODE:

## **FEATURES AND BENEFITS**

- Certified to AS/NZS 1716:2012 Respiratory Protective Devices.
- P2 disposable respirator for protection against mechanically & thermally generated particles.
- Lightweight cupped design for comfortable extended wear.
- Dual QuickLock head strap for ease of donning & doffing.
- ProValve exhalation valve for decreased breathing resistance & heat stress.
- Flexible outer mesh resists collapsing in heat & humidity.
- Resealable bag for hygienic storage.

#### **AVAILABLE IN**

PRODUCT CODE	QUANTITY	CARTON
PC822-3	3 pieces	30 boxes
PC822	12 pieces	20 boxes

## **PRODUCT DETAILS**

Straps: Textile Elastic / LLDPE Mask Lining: Terylene + PU

Outer Mesh: EVA + LDPE Filter Media: Polypropylene Melt-Blown

Weight:  $26.5g \pm 2$ 

# **CARE INSTRUCTIONS**

Shelf life of the unopened product is 3 years from date of manufacture

Ensure mask is correctly fitted prior to each use & conduct annual

## **WARNINGS AND USE LIMITATIONS**

- 1. Facial hair has the potential to compromise the required protective seal of the respirator.
- 2. Ensure adequate oxygen levels are present.
- 3. Ensure the contamination is known and the respirator is suitable for the application.
- 4. Replace when taste, smell or the breathing resistance is high.
- 5. Store in a clean resealable storage device.

## **STANDARDS**

AS/NZS 1716:2012 Respiratory Protective Devices Certified by Benchmark

To be used in conjunction with: AS/NZS 1715:2009 -Selection, use & maintenance of respiratory protective equipment



CLASSIFICATION	EFFICIENCY	EXAMPLE OF CONTAMINANTS/USES
P1	80% (Particles to 1μm micron = 0.001mm size)	Dust
P2	94% (particles to 0.3µm micron = 0.0003mm size)	Toxic dusts including asbestos, welding fumes
P3	99.95% (particles to <0.3µm micron = less than 0.0003mm size)	Toxic dusts including asbestos, welding fumes, full face and powered air performance at P3 only

when stored within temperature range of -20°C to +25°C & less than 80%

Manufactured date printed onto filters, maximum life span is 6 months once filter is removed from original packaging, however life span is determined by the wearers ability to taste, smell or notice increase in breathing resistance.

fit testing in accordance with AS/NZS 1715:2009.

# **RELATED PRODUCTS**

PRODUCT CODE:



**DUST MASKS PROMESH** P2+VALVE+CARBON

PRODUCT CODE:



MAXI MASK 2000 HALF MASK RESPIRATOR **BODY ONLY** 

PRODUCT CODE:



ASSEMBLED HALF MASK WITH A1P2 FILTERS

PRODUCT CODE:



FILTERSPEC REPLACEMENT P2+VALVE+CARBON

PRODUCT CODE:



**DUST MASKS** P2+VALVE+CARBON

AUSTRALIA: 1800 770 723

**NEW ZEALAND:** 0800 770 723 NZ@PARAMOUNTSAFETY.CO.NZ

ADELAIDE: (613) 9764 9900 SA@PARAMOUNTSAFETY.COM.AU

(617) 3806 2699 QLD@PARAMOUNTSAFETY.COM.AU

MELBOURNE: (613) 9764 9900 VIC@PARAMOUNTSAFETY.COM.AU

(618) 9301 7888 WA@PARAMOUNTSAFETY.COM.AU

(612) 9601 3877 NSW@PARAMOUNTSAFETY.COM.AU

PROCHOICESAFETYGEAR.COM

