

## Emergency Exit Device with LED indication

This unit operates the same way as the standard Em Rex<sup>®</sup> (Emergency Exit Device) but it also has two bi-colour LEDs that give three levels of indication.


It is ideally suited to locations where there is limited lighting or you need to indicate that the unit is operational (Heartbeat).

### Features:

- ▼ No breaking of glass when operated
- ▼ Two outputs: one set to break lock power and one set for status monitoring
- ▼ Visual confirmation of activation of both Em Rex Unit and Em Cover when fitted
- ▼ Visual confirmation of activation of both Em Rex Unit and Em Cover when fitted
- ▼ Audible confirmation of activation
- ▼ Ancillary input for remote operation of sounder
- ▼ Minimal moving parts
- ▼ Complies with local codes for emergency egress
- ▼ LED indication for areas where there is limited lighting, allowing the unit to be easily located
- ▼ Field resettable unit. A reset tool is supplied with every unit



### Specifications:

- ▼ Single gang profile fits standard electrical flush box
- ▼ Power requirements 9 to 16Vdc (only if using on-board sounder)
- ▼ 10mA at 13.6 Vdc
- ▼ Two sets of Clean N/C outputs (Open upon activation)
- ▼ The contacts are rated at 1 Amp @ 30Vdc
- ▼ LED indication of operation
- ▼ The face plate will not deteriorate over time and is easily cleaned
- ▼  C-Tick Certified & complies with BS 5839 Pt 2. Standard for "Break-Glass Panels"

### Product Code:

- ▼ Smart Em