


**TECHNICAL SPECIFICATIONS**

<b>Trade name</b>	Powder funnel
<b>Use</b>	Autoclavable funnel; large bore avoids bridging of powders during transfer.
<b>Material</b>	Polypropylene PP

**DIMENSIONAL SPECIFICATIONS**

<b>Diameter</b>	mm. 60,00
<b>Diameter, stem</b>	mm. 15,00
<b>Stem lenght</b>	mm. 18,00
<b>Capacity</b>	45 ml
<b>General dimensional tolerance</b>	mm. +/- 2,00

**GENERAL FEATURES**

<b>CE mark</b>	No
<b>Autoclavability</b>	Yes
<b>Sterile</b>	No
<b>Food contact suitability of the raw material</b>	Yes

**CHEMICAL RESISTANCE**

Categories of substances	Reference	Concen. %	T. 20°	T. 40°	T.° 60
<b>Inorganic acid</b>	Sulphuric acid	98	B	C	-
<b>Organic acid</b>	Benzoic acid	100	A	B	B
<b>Alcohol</b>	Ethanol	100	A	A	A
<b>Aldehydes</b>	Acetaldehyde	100	B	C	-
<b>Inorganic alkali</b>	Sodium hydroxide	50	A	A	A
<b>Organic alkali</b>	Aniline	100	A	B	C
<b>Ketone</b>	Acetone	100	-	-	-
<b>Esther</b>	Ethyl acetate	100	B	B	C
<b>Hydrocarbons, halogenated</b>	Dichloroethylene	100	C	-	-
<b>Hydrocarbons, aromatic</b>	Benzene	100	B	C	-
<b>Hydrocarbons, linear</b>	Hexane	100	B	B	C
<b>Supersolvent</b>	Tetrahydrofuran	100	B	B	C

**Legenda** (not applicable if neglected):

- **A: fair resistance;** exposure (30 days) to the chemical does not cause any damage.
- **B: sufficient resistance;** exposure causes damage of poor importance, which sometimes is only temporary.
- **C: poor resistance;** exposure to chemical is not allowed, or causes immediate permanent damage.

Results of testing with reference materials are to be considered as indication: in case of specific use it is recommended to carry out preliminary testing.

**PACKAGING**

Bag	Pcs. 10
Case	Pcs. 80

**Quality Assurance**