SUPERLIFT

REMOTE ORDERING OPTIONS



COMPATIBLE WITH







O-TX4



SL4BRM





SLEUROTX



C-TX4

AP-TX4

TX4-2

Remote Programming Steps

Programming Remotes to Receiver

- 1. Press the learn button once and immediately release (A light on the motor will illuminate)
- 2. Press the button on the new remote you wish to operate the door once (The light on the motor will extinguish)
- 3. Press the same button on the new remote a second time (the light on the motor will begin to flash rapidly)
- 4. Once the light stops flashing, press the button on the new remote a third time and it will operate the door
- 5. If the remote did not successfully code to the motor and you only get a continuous flashing light on the motor, you may have held the learn button down too long. Open and close the door four times using an existing remote and try code in the new remote again

Deleting All Remotes from Receiver

1. To delete codes from the reciver press and hold the "Code" button for approx. 6 seconds. (A "C" will display on the LED screen indicating all transmitter codes have been deleted)

RECEIVER COMPATIBILITY

Suits Models:

SDO-5 SuperLift Garage remote is suitable for most Superlift garage motors as well as 4 button "Airport", 4 button "Avanti" & 4 button "Centurion" Garage remotes.

Whilst every effort has been made to ensure the accuracy of the information supplied herein, we assume no liability for any errors or omissions. Information contained in this document is subject to change without prior notice.