GRAFIYP









Signmaking films

200-300 SERIES

POLYMERIC

grafityp.com

200-300 SERIES

The Grafitack 200/300 series is a range of flexible polymeric calendered PVC films for long term outdoor applications (up to 7 years) on an even or slightly curved surface.

The Grafitack 200/300 series is supplied on a 120 gram silicone release liner. A high-quality solvent based permanent acrylic adhesive guarantees perfect adhesion on all kinds of surfaces. (Either with or without air escape technology)

The Grafitack 200/300 series was developed for all outdoor applications up to 7 years, when applied on a flat, unribbed background, such as sign making on cars, boats and trucks, for long term decorations on shop windows and advertisement boards. It is also perfect for everyday advertising indoors and outdoors.

A wide range of sparkling colours guarantees a magnificent end result time and time again.



		TEST METHOD	200-300	1225-1226	METALLICS
1	Thickness	Din53370 (μm)	75	50	75
2	Elongation at break in length direction Elongation at break in cross direction	Din53455 (%)	> 150 > 150	> 150 > 150	>150 >150
3	Dimensional stability (on aluminium 10x10cm)	Finat 14 (mm)	< 0.40	< 0.40	< 0.40
4	Degree of gloss	Finat14 (gloss units)	min. 50 (meas. angle 20°)	min. 60 (meas. angle 20°)	min. 50 (meas. angle 60°)
5	Adhesion strength after 20 min. Adhesion strength after 24 hours	Finat 1 (N/25mm)	13 16	14 16	12 15
6	Quickstick	Finat 9 (N/625mm)	9	11	9
7	Outdoor life span (Central European conditions)	-	up to 7 years 1266 up to 3 years	Not applicable	up to 3 years
8	Temperature range at application Temperature range at use	-	+5°C to +40°C -15° to +90°C	+5°C to +40°C -15° to +90°C	+5°C to +40°C -15°C to +90°C

Signmaking films

200-300 series

POLYMERIC



