



TASKI®

Pinnacle ProX



F2

Sealer/Finish - Ultra High Speed

Description

TASKI Pinnacle ProX is a heavy duty premium performance UHS floor finish that provides exceptional “wet look” gloss, low marking and ease of maintenance. TASKI Pinnacle ProX is easy to apply and maintain with choice of a restorer system if needed.

Precautions

- Do not dilute.
- Do not use on surfaces colder than 10°C.
- To avoid contamination, do not return unused finish to original container.
- Not intended for outdoor use.

Excellent performance

- Provides a superior “wet look” gloss with diamond like brilliance and clarity.
- Great burnish response that “pops” with propane, battery or electric equipment.
- Durable, heavy duty formulation.
- Superior resistance to dirt embedment, scratching, scuffing and marking.

Easy-to-use

- Easy to apply using standard mop or applicator.
- Enables flexibility in maintenance procedures and burnishing frequency while still maintaining a great appearance.
- Can be used on most types of floors and is easy to maintain.
- Product does not contain intentionally added PFAS.

Designed for

- Retail
- Education
- Government
- Healthcare
- Institutional Facilities



NO INTENTIONALLY
ADDED PFAS**

**TASKI®****Pinnacle ProX****F2****Directions for use****Application**

1. Blockade areas to be stripped or finished. Strip old coatings using a Diversey stripper according to label directions. Allow floor to dry.
2. Apply one coat of TASKI Pinnacle ProX using a clean finish mop.
3. Allow coat to dry for 30-45 minutes depending on drying conditions. Temperature, humidity and ventilation may affect drying time.
4. Repeat steps 2 & 3 to apply 3-6 further coats for the desired gloss. Allow 30-45 minutes drying time between coats. Allow finish to cure for 24 hours before burnishing

Maintenance

1. Dust mop or sweep to remove dust or dirt.
2. Clean the floor with a mop or an automatic scrubber using the recommended Diversey brand cleaner according to label directions.
3. Maintain gloss by periodic recoating and UHS burnishing using an approved pad. Speed 1500-3000 rpm.
4. TASKI Pinnacle ProX can also be maintained periodically with a Diversey brand maintainer according to label directions. Burnish using appropriate pads.

Recoating

1. Dust mop or sweep to remove dust or dirt.
2. Deep scrub the floor with a mop or an automatic scrubber.
3. When dry, blockade area and apply 2-3 uniform coats of TASKI Pinnacle ProX using a clean finish mop.
4. Allow 30-45 minutes drying time between coats. Temperature, humidity and ventilation may affect drying time. Allow finish to cure for 24 hours before burnishing. Coverage: 50-60 m2 per litre

Note: Floors will be slippery when wet or contaminated with foreign materials. Promptly clean up spills and foreign materials.

Slip Resistance Classification D1 per AS 4586:2013

Technical data

Appearance	Opaque liquid	Specific Gravity (20°C)	1.03
Odour	Characteristic odour	pH (concentrate)	8.5
Coverage	50 – 60m ² per litre	Slip classification	D1 (AS 4586:2013)
Maintenance speed	1500 – 3000+ rpm	Dilution	Neat

The above data is typical of normal production and should not be taken as a specification.

Product	Pack size	SKU Code	Availability
TASKI Pinnacle ProX	2 x 5L	9300954	AU & NZ

Safe handling and storage information

Full guidance on the handling and disposal of this product is provided in a separate Safety Data Sheet. Store in original container. Avoid extremes of temperature and humidity. Do not dilute. To avoid contamination, do not return unused finish to original container.

Product compatibility

Under recommended conditions of use, TASKI Pinnacle ProX is suitable for use on most floor types. Non-resilient (porous) floors must be sealed first before applying finish. Ideal for low maintenance, ultra high speed program. Do not use on surfaces colder than 10°C. Not intended for outdoor use.

Safety Reminder

Please make sure your employees read and understand the product label and Safety Data Sheet before using this product. The label contains directions for use, and both the label and SDS contain hazard warnings, precautionary statements and first aid procedures. SDSs are available online at www.diversey.com or by calling Toll free: Australia, 1800 647 779 or New Zealand, 0800 803 615.

For additional information, please contact us at:
Diversey Australia Pty Ltd Toll free: 1800 647 779, Diversey New Zealand Ltd Toll free: 0800 803 615 www.diversey.com.

© 2025 Diversey, Inc. All Rights Reserved. Legal disclaimer: The associated products or services are manufactured by or otherwise emanate from Diversey Companies and their subsidiaries and not from Sealed Air.

Feb-25