



# TASKI®

# Vectra ProX



## Floor Finish

### Description

TASKI® Vectra® ProX Floor Finish saves time while giving floors diamond-like brilliance, clarity and durability.

### Features

- Can be used as a scrub and recoat finish.
- Resists scuffing, dirt and marking.
- TASKI® Vectra ProX gives high levels of gloss, durability and good levelling.
- Suitable for most types of floors.
- Easy to maintain.
- Versatile finish responds well to 175 - 1500 RPM buffing / burnishing machines
- Solids content 19%. Product does not contain intentionally added PFAS

### Benefits

- TASKI® Vectra ProX is fast curing and extremely hard, with excellent adhesion and scuff resistance which reduces the need for recoats, saving time and labour.
- Resists black heel marks and scuffs.
- Responds well to spray buffing which means floor will retain its gloss for longer between recoats.
- Excellent gloss and clarity ensuring long term floor appearance.

### Application areas

- Retail
- Education
- Government
- Healthcare
- Institutional Facilities





# TASKI®

# Vectra ProX



## Floor Finish

### Directions for use

Blockade areas to be stripped or finished. Floors will be very slippery until dry. Position wet-floor signs around area to be cleaned.

### Application:

1. Strip floor using recommended Diversey brand stripper according to label directions.
2. Apply 4 uniform coats using a clean mop. If higher gloss is desired apply additional coats.
3. Allow at least 30 minutes drying time. Temperature, humidity and ventilation affect drying time.

### Maintenance:

1. Dust, mop or sweep.
2. Clean floor using recommended Diversey brands cleaner according to label directions.
3. If desired, spray buff or high speed spray buff using recommended Diversey brand floor maintainer to enhance gloss.

### Before recoating:

1. Dust mop or sweep.
2. Deep scrub floor using recommended Diversey brand cleaner according to label directions.
3. Apply 2 coats using a clean mop.

### For best results:

- Do not dilute.
- Do not use on surfaces colder than 10°C .
- Temperature, humidity and ventilation may affect drying time.
- Allow finish to cure for 24 hours before buffing.
- To avoid contamination, do not return unused product to original container.
- Not intended for use in outdoor areas.

Technical data			
Appearance	Opaque off white liquid	Odour	Ammonia
pH (neat)	9	Specific gravity (20°C)	1.03
Coverage	50 – 60m <sup>2</sup> per litre	Slip classification	D1 (AS 4586:2013) Dry slip resistance classification)
Maintenance speed	175 – 1500 rpm	Dilution	Neat

*The above data is typical of normal production and should not be taken as a specification.*

Product	Pack size	SKU Code	Availability
TASKI® Vectra ProX	2 x 5L	9300932	AU & NZ

### Safe handling and storage information

Full guidance on the handling and disposal of this product is provided in a separate Safety Data Sheet.  
Store in original container. Avoid extremes of temperature and humidity.

### Product compatibility

Under recommended conditions of use, TASKI® Vectra ProX is suitable for use on most floor types. Non-resilient (porous) floors must be sealed first before applying finish. Ideal for low maintenance, spray buffing program. Not intended for use on cork, wood, or bamboo flooring.

### Safety Reminder

Please make sure your employees read and understand the product label and Safety Data Sheet before using this product. The label contains directions for use, and both the label and SDS contain hazard warnings, precautionary statements and first aid procedures. SDSs are available online at [www.diversey.com](http://www.diversey.com) or by calling Toll free: Australia, 1800 647 779 or New Zealand, 0800 803 615.

For additional information, please contact us at:

Diversey Australia Pty Ltd Toll free: 1800 647 779, Diversey New Zealand Ltd Toll free: 0800 803 615 [www.diversey.com](http://www.diversey.com).

Legal disclaimer: The associated products or services are manufactured by or otherwise emanate from Diversey Companies and their subsidiaries and not from Sealed Air.