



# INNERLUBE

## Friction Reducing Chain & Cable Lubricant

Penetrates, Lubricates & Protects to Increase Chain & Cable Life

- PENETRATES
- CONTAINS SOLUMOL™
- DISPLACES WATER
- NO LEAD OR CHLORINATED SOLVENTS
- DRY TO TOUCH
- CONTAINS RUST AND CORROSION INHIBITORS

### FEATURES AND BENEFITS

- Extends Cable Life - Penetrates to provide extra protection in critical wear and stress areas. Protects against wire rope fatigue and stretching by lubricating the strands.
- Extreme Pressure Protection - Innerlube contains Solumol™ which is a synthetic Molybdenum Disulphide additive that provides extreme pressure protection.
- Prevents Corrosion - Innerlube contains rust and corrosion inhibitors to protect from all weather conditions even salt water.
- Dry to Touch - Innerlube penetrates every strand then dries to protect against dust dirt and moisture.



### AREAS OF USE

- Cranes
- Mooring Lines
- Drive Chains
- Conveyors
- Chains
- Wire Rope
- Cables
- Draglines
- Forklifts

### TECHNICAL DATA

<b>RUST TEST</b>	Pass (ASTM D665)
<b>SALT SPRAY 500 Hrs</b>	Pass
<b>TIMKEN OK</b>	30kg (60lb) (ASTM D2509)
<b>POUR POINT</b>	-30°C

For more Technical Data, please refer to Safety Data Sheet of the product.

Consult the label for full instructions and precautions before using this product

**NCH AUSTRALIA PTY. LTD.** (ABN 19 000 609 316)  
5-9 Ralph Street, Alexandria, NSW 2015  
T +61 2 9669 0260 F +61 2 9693 1562 [www.nchaustralia.com](http://www.nchaustralia.com)  
©NCH Corporation 2016

To re-order, call +61 2 9669 0260 [www.nchaustralia.com](http://www.nchaustralia.com)



## WIRE ROPE COVERAGE

CABLE SIZE	METRES/LITRES
3mm (1/8")	172
6mm (1/4")	86
9.5mm (3/8")	57
12.5mm (1/2")	43
16mm (5/8")	34
19mm (3/4")	28.5
22mm (7/8")	24.5
25mm (1")	21.5
28.5mm (1 1/8")	19
32mm (1 1/4")	17
35mm (1 3/8")	15.5
38mm (1 1/2")	14.5
41mm (1 5/8")	13
44.5mm (1 3/4")	12
27.5mm (1 7/8")	11.5
51mm (2")	11

For more Technical Data, please refer to Safety Data Sheet of the product.

Consult the label for full instructions and precautions before using this product

**NCH AUSTRALIA PTY. LTD.** (ABN 19 000 609 316)

5-9 Ralph Street, Alexandria, NSW 2015

**T** +61 2 9669 0260 **F** +61 2 9693 1562 **www.nchaustralia.com**

©NCH Corporation 2016

To re-order, call +61 2 9669 0260 [www.nchaustralia.com](http://www.nchaustralia.com)

**NCH**