



DRI-GUARD PLUS

Dry Moly Lubricant

Adheres & Lubricants in High-Pressure, High-Temperature & High-Load Conditions

- LUBRICATES
- DRIES FAST
- HIGH TEMPERATURE
- NO RESIDUE
- ADHERES TO METAL SURFACES
- DOES NOT CONTAIN 1,1,1 - TRICHLORETHANE

FEATURES AND BENEFITS

- Dries Fast - dries to a non-tacky finish that protects treated surfaces from dust and dirt sticking to it.
- Adheres to Metal Surfaces - Safe to use on all metals and actually plates itself to a clean metal surfaces.
- Forms a Lubricating Protective Film - Excellent for protecting metals where it is not possible to use paint or surface coating. It effectively seals out moisture and resists water, oil, alkalis and most acids.
- Effective at Extreme Temperatures - Remains effective at temperatures from -73°C up to 399°C.



APPLICATION

- Conveyors
- Pressed Fittings
- Guides & Slides
- Slider Bearings
- Gears & Chains
- Pulleys & Reels
- Drill Presses
- Dies & Cams

TECHNICAL DATA

DOES NOT CONTAIN	Silicone or Graphite
CONSTANT SERVICE TEMP	Up to 198°C
INTERMITTENT SERVICE TEMP	Up to 349°C

For more Technical Data, please refer to Safety Data Sheet of the product.

Notice: DRI-GARD PLUS is effective up to temperatures of 399°C. However, it will begin to burn off the surface at temperatures from 349°C to 399°C. Consult the label for full instructions and precautions prior to using this product.

NCH AUSTRALIA PTY. LTD. (ABN 19 000 609 316)
5-9 Ralph Street, Alexandria, NSW 2015
T +61 2 9669 0260 F +61 2 9693 1562 www.nchaustralia.com
©NCH Corporation 2016

To re-order, call +61 2 9669 0260 www.nchaustralia.com

