

Diversey™



F&B

Fleet

Premium Vehicle Wash

Description

FLEET is a highly concentrated opaque blue liquid vehicle wash detergent based on a blend of surfactants, alkali builders, soil suspending agents and corrosion inhibitors. It is safe on most metals and painted surfaces and is extremely free rinsing and streak free even if allowed to dry on the surface.

FLEET has been formulated for the removal of a wide variety of soils from exteriors of trucks, buses, cars and buildings. Soils would include grease, oil, carbon and mud.

Features and Benefits

- Dislodges and removes ingrained vehicle grime
- Excellent for use on truck bodies, trailers, tankers, glass, earthmoving equipment, engines and chassis.
- Cleans tarpaulins and tyres to a brilliant finish
- Safe on all surfaces.
- Free rinsing - will not streak.
- Suitable for use in soft or hard water.
- Can be applied through a foaming unit.
- Mild detergent ensures operator safety





DiverseyTM

F&B

Fleet

Premium Vehicle Wash

Use Instructions:

MANUAL CLEANING: Rinse surface to remove any excess soil. Dilute 1 part to 80 parts water or 1 part to 20 parts water for heavy duty cleaning, in a bucket for vehicles and equipment cleaning. Apply by mop or sponge then rinse off with clean water.

HIGH / LOW PRESSURE SPRAYER: Rinse surface to remove any excess soil. Use at a concentration of 1:80 (dilution rate will be dependent on the degree of soilage) then rinse off with clean water. If pressure rinsing use at least 500psi pressure starting from the bottom up. Finishing with a final rinse from the top down.

LOW VOLUME FOAMING: Adjust unit to produce a concentration of 1 part to 50 parts through foaming wand. Allow 10-15 minutes dwell time then rinse off with clean water.

Avoid solution drying on surface.

Technical Data Table

Appearance	Opaque Blue Liquid
pH (neat)	≈ 9

The above data is typical of normal production and should not be taken as a specification.

Safe handling and storage information

Store in original closed containers or (where applicable) in approved bulk tank, away from sunlight and extremes of temperature. Full guidance on the handling and disposal of this product is provided in a separate Safety Data Sheet.

Product compatibility

Under recommended conditions of use, FLEET is suitable for use on most materials commonly encountered.

Safety Reminder

Please make sure your employees read and understand the product label and Safety Data Sheet before using this product. The label contains directions for use, and both the label and SDS contain hazard warnings, precautionary statements and first aid procedures. SDSs are available online at www.diversey.com or by calling Toll free: Australia, 1800 647 779 or New Zealand, 0800 803 615.

For additional information, please contact us at:
Diversey Australia Pty Ltd Toll free: 1800 647 779, Diversey New Zealand Ltd Toll free: 0800 803 615 www.diversey.com.

© 2023 Diversey, Inc. All Rights Reserved.