

## Hazardous, Dangerous Goods

## 1. MATERIAL AND SUPPLY COMPANY IDENTIFICATION

Product name: Kemsol Stain-Enz

Recommended use: Enzyme Laundry Spotter Treatment

**Supplier:** Chemical Solutions Limited - Kemsol

Company No.:

Street Address: 1 Freight Place

Airport Oaks Auckland 2022 New Zealand (64-9) 255-5609

 Telephone:
 (64-9) 255-5609

 Facsimile:
 (64-9) 255-5610

 Email:
 sales@kemsol.co.nz

Emergency Telephone number: 0800-764-766 National Poisons Centre NZ

## 2. HAZARDS IDENTIFICATION

This material is hazardous according to criteria of EPA New Zealand.

EPA Group Standard: HSR002528 - Cleaning Products (Flammable) Group Standard





## Signal Word

Danger

## **Hazard Classifications**

3.1C - Flammable liquids

6.3B - Substances that are mildly irritating to the skin

6.4A - Substances that are irritating to the eye

6.5A - Substances that are respiratory sensitisers

#### **Hazard Statements**

H226	Flammable liquid and vapour.
H316	Causes mild skin irritation.
H319	Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

## **Prevention Precautionary Statements**

P102	Keep out of reach of children.
P103	Read carefully and follow all instructions.
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical, ventilating, lighting and all other equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P261	Avoid breathing mist, vapours or spray.

Product Name: Kemsol Stain-Enz Reference No: FK-STAENB

Issued: 2021-07-16 Version: 002 Page 1 of 8



P264 Wash hands thoroughly after handling.

P280 Wear protective gloves/protective clothing including eye/face protection and suitable

respirator.

P285 In case of inadequate ventilation wear respiratory protection.

## **Response Precautionary Statements**

P101 If medical advice is needed, have product container or label at hand.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a

position comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P332+P313 If skin irritation occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTRE or doctor/physician. P370+P378 In case of fire: Use (water, alcohol resistant foam or dry agent (carbon dioxide, dry

chemical powder)) to extinguish.

#### Storage Precautionary Statement

P403+P235 Store in a well-ventilated place. Keep cool.

## **Disposal Precautionary Statement**

P501 Dispose of contents/container in accordance with local, regional, national and

international regulations.

## DANGEROUS GOOD CLASSIFICATION

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

Dangerous Goods Class: 3

## 3. COMPOSITION INFORMATION

CHEMICAL ENTITY	CAS NO	PROPORTION
Water Ingredients determined to be non-hazardous or below reporting limits Propanol, (2-methoxymethylethoxy)-	7732-18-5 34590-94-8	30-50 % 10-20 % <10 %
Isopropyl alcohol Surfactants Subtilisin	67-63-0 9014-01-1	10-20 % <10 % 1-3 %
Ingredients determined to be Non-Hazardous	9014-01-1	Balance
		100%

#### 4. FIRST AID MEASURES

Issued: 2021-07-16

If poisoning occurs, contact a doctor or Poisons Information Centre (Phone Australia 131 126, New Zealand 0800 764 766).

**Inhalation:** Effects may be delayed. Remove victim from exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If breathing laboured and patient cyanotic (blue), ensure airways are clear and have a qualified person give oxygen through a facemask. If breathing has stopped apply artificial respiration at once. In the event of cardiac arrest, apply external cardiac massage. Seek immediate medical

Product Name: Kemsol Stain-Enz Reference No: FK-STAENB

Version: 002

Page 2 of 8



advice.

**Skin Contact:** If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If swelling, redness, blistering or irritation occurs seek medical assistance. For gross contamination, immediately drench with water and remove clothing. Continue to flush skin and hair with plenty of water (and soap if material is insoluble). For skin burns, cover with a clean, dry dressing until medical help is available. If blistering occurs, do NOT break blisters. If swelling, redness, blistering, or irritation occurs seek medical assistance.

**Eye contact:** If in eyes, hold eyelids apart and flush the eyes continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a Doctor; or for at least 15 minutes and transport to Doctor or Hospital.

**Ingestion:** Rinse mouth with water. If swallowed, do NOT induce vomiting. Give a glass of water to drink. Never give anything by the mouth to an unconscious patient. If vomiting occurs give further water. Seek medical advice.

**PPE for First Aiders:** Wear overalls, gloves, safety glasses. Available information suggests that gloves made from butyl rubber, natural rubber, nitrile rubber, neoprene, polyvinyl chloride (PVC) should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Notes to physician: Treat symptomatically. Effects may be delayed.

#### 5. FIRE FIGHTING MEASURES

Hazchem Code: •3Y

**Suitable extinguishing media:** If material is involved in a fire use alcohol resistant foam or dry agent (carbon dioxide, dry chemical powder).

**Specific hazards:** Flammable liquid and vapour. May form flammable vapour mixtures with air. Flameproof equipment necessary in area where this chemical is being used. Nearby equipment must be earthed. Electrical requirements for work area should be assessed according to AS3000. Vapour may travel a considerable distance to source of ignition and flash back. Avoid all ignition sources. All potential sources of ignition (open flames, pilot lights, furnaces, spark producing switches and electrical equipment etc) must be eliminated both in and near the work area. Do NOT smoke.

**Fire fighting further advice:** Heating can cause expansion or decomposition leading to violent rupture of containers. If safe to do so, remove containers from path of fire. Keep containers cool with water spray. On burning or decomposing may emit toxic fumes. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion or decomposition.

## **6. ACCIDENTAL RELEASE MEASURES**

#### **SMALL SPILLS**

Wear protective equipment to prevent skin and eye contamination. Avoid inhalation of vapours or dust. Wipe up with absorbent (clean rag or paper towels). Collect and seal in properly labelled containers or drums for disposal.

#### LARGE SPILLS

If safe to do so, shut off all possible sources of ignition. Clear area of all unprotected personnel. Slippery when spilt. Avoid accidents, clean up immediately. Wear protective equipment to prevent skin and eye contamination and the inhalation of vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Use a spark-free shovel. Collect and seal in properly labelled containers or drums for disposal. If contamination of crops, sewers or waterways has occurred advise local emergency services.

Product Name: Kemsol Stain-Enz Reference No: FK-STAENB

Issued: 2021-07-16 Version: 002 Page 3 of 8



Dangerous Goods - Initial Emergency Response Guide No: 14

## 7. HANDLING AND STORAGE

Handling: Avoid eye contact and repeated or prolonged skin contact. Avoid inhalation of vapour, mist or aerosols.

Storage: Store in a cool, dry, well-ventilated place and out of direct sunlight. Store away from foodstuffs. Store away from incompatible materials described in Section 10. Store away from sources of heat and/or ignition. Keep container standing upright. Keep containers closed when not in use - check regularly for leaks.

This material is classified as a Class 3 Flammable Liquid as per the criteria of the "New Zealand NZS5433: Transport of Dangerous Goods on Land" and/or the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and must be stored in accordance with the relevant regulations.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### National occupational exposure limits:

	TWA		STEL		NOTICES
	ppm	mg/m3	ppm	mg/m3	
Dipropylene glycol methyl ether Isopropyl alcohol	100 400	606 983	150 500	909 1,230	(skin)
Subtilisins (Proteolytic enzymes, as 100% pure crystalline enzyme)	400	Ceiling 0.00006	300	1,230	(skin)

As published by WorkSafe New Zealand.

WES-TWA (Workplace Exposure Standard - Time-weighted average). The average airborne concentration of a substance calculated over an eight-hour working day.

WES-Ceiling (Workplace Exposure Standard - Ceiling). A concentration that should not be exceeded at any time during any part of the working day.

WES-STEL (Workplace Exposure Standard - Short-term exposure limit). The 15-minute time weighted average exposure standard. Applies to any 15-minute period in the working day and is designed to protect the worker against adverse effects of irritation, chronic or irreversible tissue change, or narcosis that may increase the likelihood of accidents. The WES-STEL is not an alternative to the WES-TWA; both the short-term and timeweighted average exposures apply. Exposures at concentrations between the WES-TWA and the WES-STEL should be less than 15 minutes, should occur no more than four times per day, and there should be at least 60 minutes between successive exposures in this range.

(skin) - Skin absorption. Skin absorption—applicable to a substance that is capable of being significantly absorbed into the body through contact with the skin.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept too as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

Biological Limit Values: As per the WorkSafe New Zealand the ingredients in this material do not have a Biological Limit Allocated.

**Product Name: Kemsol Stain-Enz** Reference No: FK-STAENB Issued: 2021-07-16

Version: 002

Page 4 of 8



**Engineering Measures:** Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Use only in well ventilated areas. Use with local exhaust ventilation or while wearing appropriate respirator.

Personal Protection Equipment: OVERALLS, GLOVES, SAFETY GLASSES.

Personal protective equipment (PPE) must be suitable for the nature of the work and any hazard associated with the work as identified by the risk assessment conducted.

Wear overalls, gloves, safety glasses. Available information suggests that gloves made from butyl rubber, natural rubber, nitrile rubber, neoprene, polyvinyl chloride (PVC) should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

**Hygiene measures:** Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid contact with clothing. Avoid eye contact and repeated or prolonged skin contact. Avoid inhalation of vapour, mist or aerosols. Ensure that eyewash stations and safety showers are close to the workstation location.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Material Family: Aqueous Formulation

Base Units: Litres
Form: Clear Liquid

Colourless - Tinge of Yellow

**Solubility in water:** Completely soluble in all proportions

Specific Gravity: 1.012 Flash Point (°C): 31

**pH:** 7.5 (100% solution)

(Typical values only - consult specification sheet) N Av = Not available, N App = Not applicable

#### **10. STABILITY AND REACTIVITY**

Chemical stability: This material is thermally stable when stored and used as directed.

Conditions to avoid: Elevated temperatures and sources of ignition.

**Incompatible materials:** Oxidising agents.

**Hazardous decomposition products:** Oxides of carbon and nitrogen, smoke and other toxic fumes.

Hazardous reactions: No known hazardous reactions.

## 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

#### **Acute Effects**

Inhalation: Material may be an irritant to mucous membranes and respiratory tract. A respiratory sensitiser. Can

Product Name: Kemsol Stain-Enz

Reference No: FK-STAENB

Issued: 2021-07-16

Version: 002

Page 5 of 8



cause possible allergic reactions.

**Skin contact:** Contact with skin may result in irritation. Will have a degreasing action on the skin. Repeated or prolonged skin contact may lead to irritant contact dermatitis.

Ingestion: Swallowing can result in nausea, vomiting and irritation of the gastrointestinal tract.

Eye contact: An eye irritant.

#### **Acute toxicity**

**Inhalation:** This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): LC50 > 20.0 mg/L for vapours or LC50 > 5.0 mg/L for dust and mist or LC50 > 5,000 ppm gas

**Skin contact:** This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >5,000 mg/Kg bw

**Ingestion:** This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >5,000 mg/Kg bw

**Corrosion/Irritancy:** Eye: this material has been classified as a 6.4A - Substances that are irritating to the eye. Skin: this material has been classified as a 6.3B - Substances that are mildly irritating to the skin.

**Sensitisation:** Inhalation: this material has been classified as a 6.5A - Substances that are respiratory sensitisers. Skin: this material has been classified as not a skin sensitiser.

Aspiration hazard: This material has been classified as non-hazardous.

Specific target organ toxicity (single exposure): This material has been classified as non-hazardous.

**Chronic Toxicity** 

Mutagenicity: This material has been classified as non-hazardous.

Carcinogenicity: This material has been classified as non-hazardous.

Reproductive toxicity (including via lactation):

This material has been classified as non-hazardous.

Specific target organ toxicity (repeat exposure): This material has been classified as non-hazardous.

#### 12. ECOLOGICAL INFORMATION

Avoid contaminating waterways.

**Acute aquatic hazard:** This material has been classified as non-hazardous. Acute toxicity estimate (based on ingredients): >100 mg/L

**Long-term aquatic hazard:** This material has been classified as non-hazardous. Non-rapidly or rapidly degradable substance for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, Acute toxicity estimate (based on ingredients): >100 mg/L, where the substance is not rapidly degradable and/or BCF < 500 and/or log  $K_{ow}$  < 4.

Ecotoxicity in the soil environment: This material has been classified as non-hazardous.

Ecotoxicity to terrestrial vertebrates: This material has been classified as non-hazardous.

Ecotoxicity to terrestrial invertebrates: This material has been classified as non-hazardous.

Product Name: Kemsol Stain-Enz

Reference No: FK-STAENB

Issued: 2021-07-16

Version: 002

Page 6 of 8



**Ecotoxicity:** No information available.

Persistence and degradability: No information available.

Bioaccumulative potential: No information available.

Mobility: No information available.

#### 13. DISPOSAL CONSIDERATIONS

Persons conducting disposal, recycling or reclamation activities should ensure that appropriate personal protection equipment is used, see "Section 8. Exposure Controls and Personal Protection" of this SDS.

If possible material and its container should be recycled. If material or container cannot be recycled, dispose in accordance with local, regional, national and international Regulations.

#### 14. TRANSPORT INFORMATION

#### **ROAD AND RAIL TRANSPORT**

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".



UN No: 1993

Dangerous Goods Class: 3

Packing Group: III

Hazchem Code: •3Y

Emergency Response Guide No: 14

Proper Shipping Name: FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL)

**Segregation Dangerous Goods:** Not to be loaded with explosives (Class 1), flammable gases (Class 2.1), if both are in bulk, toxic gases (Class 2.3), spontaneously combustible substances (Class 4.2), oxidising agents (Class 5.1), organic peroxides (Class 5.2), toxic substances (Class 6.1), infectious substances (Class 6.2) or radioactive substances (Class 7). Exemptions may apply.

## MARINE TRANSPORT

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.



UN No: 1993

Dangerous Goods Class: 3

Packing Group: III

**Proper Shipping Name:** FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL)

Product Name: Kemsol Stain-Enz Reference No: FK-STAENB

Issued: 2021-07-16 Version: 002 Page 7 of 8



#### AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.



UN No: 1993
Dangerous Goods Class: 3
Packing Group: III

Proper Shipping Name: FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL)

## 15. REGULATORY INFORMATION

## This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances)

The Stockholm Convention (Persistent Organic Pollutants)

The Rotterdam Convention (Prior Informed Consent)

Basel Convention (Hazardous Waste)

International Convention for the Prevention of Pollution from Ships (MARPOL)

 All components of this product are listed on or exempt from the New Zealand Inventory of Chemical (NZIoC).

EPA Group Standard: HSR002528 - Cleaning Products (Flammable) Group Standard

Approved handler Yes
Location test certificate Yes
Fire extinguishers Yes
Signage Yes
Emergency response Yes
Hazardous atmosphere zone

## 16. OTHER INFORMATION

Reason for issue: Format change

This information was prepared in good faith from the best information available at the time of issue. It is based on the present level of research and to this extent we believe it is accurate. However, no guarantee of accuracy is made or implied and since conditions of use are beyond our control, all information relevant to usage is offered without warranty. The manufacturer will not be held responsible for any unauthorised use of this information or for any modified or altered versions.

If you are an employer it is your duty to tell your employees, and any others that may be affected, of any hazards described in this sheet and of any precautions that should be taken.

Safety Data Sheets are updated frequently. Please ensure you have a current copy.

Product Name: Kemsol Stain-Enz Reference No: FK-STAENB

Issued: 2021-07-16 Version: 002 Page 8 of 8