

Fosroc® Primer 24

constructive solutions

(Previously known as Emer-Proof Self-adhesive Primer)

Bitumen primer for Proofex self adhesive membranes and Proofex Torchseal torch-on membranes

Uses

Fosroc Primer 24 is used to prime prepared concrete and masonry surfaces prior to the installation of Proofex self adhesive bituminous sheet waterproofing membranes and sealing tapes. Also used for priming prior to the application of Proofex Torchseal membranes.

Advantages

- Fast drying enables work to progress
- Can be applied to SSD concrete

Description

Fosroc Primer 24 is a single component, solvent based bituminous primer for concrete prior to the installation bitumen based self adhesive and torch applied membranes.

Properties.

Appearance:	Brown/Black liquid
Drying time (touch dry):	30mins @ 25°C
VOC content:	569g/L

Instructions for Use

Preparation

All surfaces to which membrane is applied must be smooth and free from contaminates and any loose material. Rough concrete should be "faired up" before membrane application

Application

Fosroc Primer 24 should be applied at the rate of 6 to 8m² per litre to surfaces which will have membrane applied. The coverage rate for the primer will vary depending on the porosity of the surface being treated. Allow the primer to dry for a minimum of 30 minutes and a maximum of 8 hours, at temperatures of 25°C and above; the primer must be touch dry. Longer drying times will be required at lower temperatures. Priming should only be carried out on surfaces which will be covered with membrane on the same day.

Cleaning

All tools and equipment should be cleaned immediately after use with Fosroc Solvent 10. Spillages should be absorbed with sand or sawdust and disposed in accordance with local regulations.

Supply

Fosroc Primer 24:	4 litre:	FC020500-4L
Fosroc Primer 24:	20 litre:	FC020500-20L

Coverage

6 - 8m² / litre

Storage

Fosroc Primer 24 has a shelf life of 24 months if kept in a cool, dry conditions in the original, unopened packs. If stored at high temperatures and/or high humidity conditions the shelf life may be reduced.

Important notice

A Safety Data Sheet (SDS) is available from the Fosroc website. Read the SDS and TDS carefully prior to use as application or performance data may change from time to time. In emergency, contact any Poisons Information Centre (phone 13 11 26 within Australia) or a doctor for advice.

Product disclaimer

This Technical Data Sheet (TDS) summarises our best knowledge of the product, including how to use and apply the product based on the information available at the time. You should read this TDS carefully and consider the information in the context of how the product will be used, including in conjunction with any other product and the type of surfaces to, and the manner in which, the product will be applied. Our responsibility for products sold is subject to our standard terms and conditions of sale. Parchem does not accept any liability either directly or any losses suffered in connection with the use or application of the product whether or not in accordance with any advice, specification, recommendation or information given by it.



*Manufactured and sold under license from Fosroc International Limited. Fosroc and the Fosroc logo are trade marks of Fosroc International Limited, used under license. Parchem Construction Supplies Pty Ltd 7 Lucca Road, Wyong NSW 2259

Ph: 1800 812 864 www.fosroc.com.au ABN 80 069 961 968

Distributed in New Zealand by: Concrete Plus Ltd 150 Hutt Park Road Gracefield Ph: 0800 657 156 www.fosroc.co.nz NZBN 9429033691282