



### Overview

Lead time	Usually in Stock
-----------	------------------

### General

Provided equipment	Installation guide Safety guide
--------------------	------------------------------------

### Physical

Colour	Black
Depth	4.7 cm
Height	52.3 cm
Net weight	1.88 kg
Width	5.6 cm

### Input

[In] rated current	16 A
Permissible voltage	100...240 V
Max line current	20 A
Input current limits	20 A
Load capacity	3300 VA
Network frequency	50/60 Hz
Plug standard	IEC 60320 C20
Input voltage	230 V

### Output

Number of power socket outlets	14 IEC 60320 C13
--------------------------------	------------------

## Conformance

Product certifications	CUL listed UL listed
------------------------	-------------------------

## Environmental

Ambient air temperature for operation	0...50 °C
Relative humidity	5...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...65 °C
Storage Relative Humidity	5...95 %
Storage altitude	0.00...15240.00 m

## Packing Units

Package 1 Weight	2.55 kg
Package 1 Height	61.2 cm
Package 1 width	12.3 cm
Package 1 Length	10.7 cm
SCC14	10731304327766
Number of Units in Package 3	96

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Lead free	Yes
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------