

# Matrix™ 2000 Standalone Inverter



## Features

- Designed for telecom applications
- Pure sine wave output
- Unity power factor (full 2000 watt output power)
- Significant overload capability, 120% continuously, 200% for 5 seconds
- High efficiency, >91%
- High power density
- Built in Static Transfer Switch (STS)
- DSP design for improved reliability and performance
- Single phase 120Vac or 230Vac output options
- Comprehensive LCD/LED with keypad
- USB interface for connecting to PC
- Wide selection of configurable parameters.
- International certifications

The **Eaton® Matrix™ 2000 Standalone Inverter** is designed for use in telecommunications applications where a very reliable AC supply is required. The high efficiency and compact size makes the Matrix 2000 Inverter an outstanding solution for powering all types of critical AC equipment.

The Matrix 2000 Standalone Inverter provides 2000W of reliable AC power in a 1U x 19" rack mount package that includes a built-in Static Transfer Switch (STS). The STS automatically and instantaneously switches the AC output, from the DC inverter to an alternative source such as AC mains (and back again), providing extra security of the AC supply to the load equipment.

The Matrix 2000 solution uses digital microprocessor control to provide maximum performance under all operating conditions. The built-in controller gives real-time system status through comprehensive LCD/LED displays, and allows program setting through a keypad panel.

The Matrix 2000 Standalone Inverter includes a built in USB interface for monitoring and control.

# Technical Specifications

## DC Input

Operating Range	48V: 40Vdc ~ 60Vdc
-----------------	--------------------

## AC Input (to Transfer Switch)

Voltage Range: (50/60Hz)	INV-4820SA: 89Vac to 138Vac
	INV-4820ESA: 176Vac to 276Vac
Transfer Time	<10ms

## AC Output

Power Output	2000VA / 2000W
Wave Form	Pure sine wave
Power Factor	1.0
Nominal Output Voltage (selectable)	INV-4820SA: 110/115/120Vac
	INV-4820ESA: 208/220/230/240Vac
Output Frequency	50,60Hz
Efficiency	>91% at rated load
Over Load Protection	2*Inom, 5sec max
	1.5*Inom, 10sec max
	1.25*Inom, temperature controlled

## Environmental Requirements

Operating Temperature Range	-20°C to 60°C (-4°F to 140°F)
	-20°C to 50 °C (-4°F to 122°F), full performance
Cooling	Fan Cooled

## Certifications

All products comply with international standards.

Safety	EN60950-1 / UL60950-1
--------	-----------------------

Europe	CE
--------	----

In the interests of continual product improvement all specifications are subject to change without notice.



## New Zealand Distributor



7 Glover Street, Ngauranga, Wellington  
59 Maurice Road, Penrose, Auckland  
PO Box 13-432, Johnsonville, Wellington  
0800 UPS POWER (0800 877 769)  
sales@upspower.co.nz  
www.upspower.co.nz



Eaton, CellSure, SiteSure, DCTools and PowerManager are trade names, trademarks, and/or service marks of Eaton Corporation or its subsidiaries and affiliates. All other trademarks are property of their respective owners.

© 2009 Eaton Corporation  
All Rights Reserved  
MTX2000 B