

IFR4000

Portable Nav/Comm Test Set

A compact, lightweight and weatherproof unit for testing ILS, VOR, Marker Beacon and VHF/UHF communications avionics systems

The most important thing we build is trust

VIAT / AVCOMM



IFR4000

Equips the maintenance technician with the most portable navigational communications ramp test set on the market today



Features

- Most portable Nav/Comm ramp tester available
- Guided Test capability cuts down total test time
- Low cost ELT option
- Frequency counter provides external frequency measurement
- Generation of ARINC 596 Selective Calling Tones
- MORSE CODE provides 1-4 characters transmitted in the VOR and ILS localizer mode
- Eight or more hours of operation before recharge
- Automatic power shut-down
- Ergonomic design

Applications

- Support for ramp or bench environment via over-the-air or direct connection
- Measurement of VHF/UHF transmitter, frequency, output power, modulation (AM and FM and receiver sensitivity)
- Measurement of HF transmitter, frequency, output power, modulation (AM and SSB USB/LSB) receiver sensitivity
- Accurate measurement of HF/VHF/UHF antenna and or feeder SWR (Standing Wave Ratio)
- Simulation of Localizer and Glideslope (CAT I, II and III Ground Station) Signals with variable DDM settings
- Swept Localizer DDM for coupled Auto Pilot testing (Simultaneous Localizer, Glideslope and Marker signals)
- Simulation of VOR Beacon with variable bearing
- Simulation of Marker Beacon, Selectable Airways (Z), Outer and Middle Marker Tones
- Signal generation of VOR, Localizer, Glideslope and Marker Beacon
- Signal generation and monitoring of COMM AM/FM/SSB
- ILS provides simultaneous Localizer, Glideslope and Marker Beacon signals
- SELCAL decoder testing
- Monitoring of Emergency Locator Transmitter (ELT), Emergency Position Indicating Radio Beacons (EPIRB) and Personal Locator Beacons (PLB)

See Product Specification Sheet for a more detailed specification.

The IFR 4000 verifies the operation and installation of ILS, VOR and Marker Beacon receivers and VHF/ UHF AM/FM and HF AM/SSB transceivers. The menu driven functionality and guided test capability make this instrument extremely easy to use.

Physical Characteristics

Size: 11.2"H x 9.1"W x 2.7"D
(28.5 cm x 23.1 cm x 6.9 cm)

Weight (test set only): 8.0 lbs. (3.6 kg)



Environmental

Use: Indoors
Altitude: ≤3,000 feet
Temperature: 5° C to 40° C

Certifications

MIL-PRF-28800F Class 2
MIL-STD-810F
CE
UL

For complete certification list, see Product Spec Sheet

VERSIONS, OPTIONS AND ACCESSORIES

Order Number	Description
72418	IFR 4000 Nav/Comm Ramp Test Set IFR 4000AR (U.S Military version w/ protective cover)
83402	4000OPT1 ELT (121.5/243 MHz beacon and 406 MHz COSPAS/SARSAT beacon test)

NSN Information:

6625-01-516-4656 (IFR 4000)
6625-01-559-2384 (IFR 4000AR)
6625-01-553-1956 (IFR 4000 with ELT option installed)

Standard Accessories

9140	Antenna, 75 MHz
9137	Antenna, telescoping
10238	Transit case
6081	Operation Manual (CD)
6087	Getting Started Manual
67366	AC/DC power supply
62302	Power cord, 110 V
64020	Power cord set, 220 V
62398	TNC (male) to TNC (male) coaxial cable
24140	TNC (female) shorting cap
56080	Spare fuse
24141	50 Ω load
63958	Flip cover (IFR 4000AR only)

Optional Accessories

63656	Desk top stand
62400	RS-232 cable
6083	Maintenance Manual (CD)

For More Information:



Vicom Australia

1064 Centre Road
Oakleigh South Vic 3167
Australia
1300 360 251
info@vicom.com.au
www.vicom.com.au

Vicom New Zealand

Grd Floor, 60 Grafton Road
Auckland 1010
New Zealand
+64 9 379 4596
info@vicom.co.nz
www.vicom.co.nz



Contact Us +1 316 522 4981
AvComm.TechSales@viasolutions.com

To reach the VIAVI office nearest you, visit
viasolutions.com/contact.

© 2018 VIAVI Solutions Inc.
Product specifications and descriptions in this document are subject to change without notice.
IFR6000-ss-avi-nse-ae
30186488 900 0618

viasolutions.com

Part No. 1015DS, Issue 2, 10/15

