



A RIPLEY® BRAND



## CFS-2

### Fibre Optic Stripper

Category: Cable Strippers

Brand: Miller®

Dual Hole Fiber Optic Stripper

## Overview

- Two hole design efficiently strips away the 1.6 to 3 mm jacket or 900 micron tight buffer & 250 micron buffer coating from the 125 micron bare fiber in one compact tool.
- All stripping surfaces are quality manufactured to precise tolerances to ensure clean, smooth strips with every use
- Factory set blade notches require no adjustment & will not scratch or nick the fiber
- Compliant thermoplastic elastomer handle grips are ergonomically designed to fit comfortably in either hand, reducing the risk of injury from the repetitive stripping function

## Specifications

<b>Length</b>	6.5" (165 mm)
<b>Weight</b>	4.2 oz (119 g)

MODEL	PART NO.
CFS-2	46107-M
CFS-2 900	81281



# CFS-2 Fiber Optic Stripper

## Operating Instructions



**Warning! This tool should not be used on live electrical circuits. It is not protected against electrical shock!** Always use OSHA/ANSI or other industry approved eye protection when using tools. This tool is not to be used for purposes other than intended. Read carefully and understand instructions before using this tool.

1. The larger stripping notch at the tip of the tool with a 1.0 mm diameter can be used to strip many fiber jackets. Close the tool around the jacket, hold firmly and strip off jacket material.
2. If there is a Kevlar® central strength member, this must be trimmed with a Kevlar cutter like the Miller 86 1/2SF Kevlar Shears or Miller FOKC.
3. The smaller stripping notch close to the pivot point is designed to remove 250µm buffer from 125µm fiber.
  - a) Insert the fiber into the smaller notch of tool
  - b) Close the tool squarely with the fiber, hold firmly
  - c) Draw the tool towards the end of the fiber exerting steady pressure. We recommend several short strips to be made to acquire the desired finished length.
4. Always make sure the fiber stripping notch is clean and clear of any debris. If not clean, the tool will break fiber rather than strip it.
5. Tool may be cleaned with Miller FS400 Bifurcated Foam Tip Swipe or a soft bristle brush.

WARRANTY: RIPLEY warrants its products against defective materials and workmanship for a period of one year from date of shipment from the RIPLEY factory provided the product is utilized in accordance with instructions and specified ratings.

### For more information:

#### Vicom Australia Pty Ltd

1064 Centre Rd. Oakleigh South Vic 3167 Australia  
1300 360 251 [info@vicom.com.au](mailto:info@vicom.com.au) [www.vicom.com.au](http://www.vicom.com.au)

#### Vicom New Zealand Ltd

Grd Floor, 60 Grafton Road AUCKLAND 1010 New Zealand  
+649 379 4596 [info@vicom.co.nz](mailto:info@vicom.co.nz) [www.vicom.co.nz](http://www.vicom.co.nz)



46 Nooks Hill Road, Cromwell, CT 06416  
860-635-2200 [www.ripley-tools.com](http://www.ripley-tools.com)

46455 rev1 11-27-12ff