

CFS-2 900

Fibre Optic Stripper



Category: Cable Strippers

Brand: Miller®

Dual Hole Fiber Optic Stripper

Overview

- Two hole design efficiently strips away the 1.6 to 3 mm jacket or 900 micron tight buffer & 250 micron buffer coating from the 125 micron bare fiber in one compact tool.
- All stripping surfaces are quality manufactured to precise tolerances to ensure clean, smooth strips with every use
- Factory set blade notches require no adjustment & will not scratch or nick the fiber
- Compliant thermoplastic elastomer handle grips are ergonomically designed to fit comfortably in either hand, reducing the risk of injury from the repetitive stripping function

Specifications

Length	6.5" (165 mm)
Weight	4.2 oz (119 g)

MODEL	PART NO.
CFS-2	46107-M
CFS-2 900	81281

For more information:

Vicom Australia Pty Ltd

1064 Centre Rd. Oakleigh South Vic 3167 Australia
1300 360 251 info@vicom.com.au www.vicom.com.au

Vicom New Zealand Ltd

Grd Floor, 60 Grafton Road AUCKLAND 1010 New Zealand
+649 379 4596 info@vicom.co.nz www.vicom.co.nz

CFS-2-900 FIBER OPTIC STRIPPER

Instruction Sheet

Warning! This tool should not be used on live electrical circuits. It is not protected against electrical shock! Always use OSHA/ANSI or other industry approved eye protection when using tools. This tool is not to be used for purposes other than intended. Read carefully and understand instructions before using this tool.



Note: This tool is a manually operated cutting device for stripping coatings from optical fiber and not intended to cut or strip wire or Kevlar®.

1. The larger stripping notch at the tip of the tool can be used to remove fiber jacket, ranging in sizes 2mm to 3mm. Grasping the tool firmly, close the tool around the jacket and strip-off the jacket material.
2. If there are Kevlar® strength members, cut them using a “Kevlar® cutter”, such as the Miller KS-1 or 86-1/2SF Kevlar® shears.
3. The smaller stripping notch closest to the pivot point is designed to remove, in a single operation, the 900µm & 250µm coatings to expose the 125µm fiber (900µm & 250µm are removed at the same time).
 - a. Insert the fiber into the small notch.
 - b. Close the tool squarely with the fiber. Close completely, but do not squeeze hard. Depending on the fiber construction, angling the tool slightly may improve the stripping.
 - c. Draw the tool towards the end of the fiber, exerting steady pressure. We recommend several short strips to achieve the desired finished length.

Note: Always make sure the fiber stripping notch is clean and clear of any debris. The tool may be cleaned using the Miller FS400 Bifurcated Foam Tip Swipes, which contain 99% isopropyl alcohol. Failure to keep the tool clean may cause the fiber to break.

WARRANTY: RIPLEY warrants its products against defective materials and workmanship for a period of one year from date of shipment from the RIPLEY factory provided the product is utilized in accordance with instructions and specified ratings.

For more information:

Vicom Australia Pty Ltd

1064 Centre Rd. Oakleigh South Vic 3167 Australia
1300 360 251 info@vicom.com.au www.vicom.com.au

Vicom New Zealand Ltd

Grd Floor, 60 Grafton Road AUCKLAND 1010 New Zealand
+649 379 4596 info@vicom.co.nz www.vicom.co.nz



46 Nooks Hill Road, Cromwell, CT 06416 USA ~ Phone: 800-528-8665 ~ Int'l: (01) 860-635-2200
Fax: (01) 860-635-3631 ~ E-mail: info@ripley-tools.com ~ Internet: www.ripley-tools.com



81287 rev1
12-01-12 ff