

# AXIS Q1715 Block Camera

High performance with endless options

AXIS Q1715 delivers HDTV 1080p at 60 fps and 21x optical zoom for all the details. With a deep learning processing unit, it's possible to take advantage of intelligent tailor-made applications based on deep learning on the edge. It comes with AXIS Object Analytics for highly nuanced object classification and reliable detection with fewer false positives. And, it provides analytics metadata based on deep learning on the edge. Lightweight in design, it's easy to install in accessory housings and casings. It offers support for 2-way audio and supervised I/O. Furthermore, it features built-in cybersecurity features to prevent unauthorized access and safeguard your system.

- > **1080p at 60 fps with 21x zoom**
- > **Support for analytics with deep learning**
- > **Granular object classification**
- > **Ideal for accessory housings and casings**
- > **HDMI and HD-SDI output**



# AXIS Q1715 Block Camera

| Camera                                   |  |
|--|--|
| <b>Image sensor</b>                      | 1/2.8" progressive scan RGB CMOS   |
| <b>Lens</b>                              | Varifocal, 4–84.6 mm, F1.6–F4.5<br>Horizontal field of view: 76°–3.6°<br>Vertical field of view: 42°–2.2°<br>Autofocus, P-Iris control   |
| <b>Day and night</b>                     | Automatically removable infrared-cut filter  |
| <b>Minimum illumination</b>              | 1080p 25/30 fps with Forensic WDR and Lightfinder 2.0:<br>Color: 0.1 lux at 50 IRE F1.5<br>B/W: 0.02 lux at 50 IRE F1.5<br>1080p 50/60 fps with Forensic WDR and Lightfinder 2.0:<br>Color: 0.2 lux at 50 IRE F1.5<br>B/W: 0.04 lux at 50 IRE F1.5   |
| <b>Shutter speed</b>                     | 1/66500 s to 2 s   |
| <b>Pan/Tilt/Zoom</b>                     | Zoom: 21x optical<br>100 preset positions, control queue, adjustable zoom speed<br>Uploadable PTZ driver   |
| System on chip (SoC)                     |  |
| <b>Model</b>                             | ARTPEC-7   |
| <b>Memory</b>                            | 2048 MB RAM, 1024 MB Flash   |
| <b>Compute capabilities</b>              | Deep learning processing unit (DLPU)   |
| Video                                    |  |
| <b>Video compression</b>                 | H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles<br>H.265 (MPEG-H Part 2/HEVC) Main Profile<br>Motion JPEG  |
| <b>Resolution</b>                        | 1920x1080 HDTV 1080p to 160x90   |
| <b>Frame rate</b>                        | Up to 60/50 fps (60/50 Hz) in all resolutions<br>HDMI and HD-SDI are limited to 30 fps in 1080p  |
| <b>Video streaming</b>                   | Multiple, individually configurable streams in H.264, H.265 and Motion JPEG<br>Axis Zipstream technology in H.264 and H.265<br>Controllable frame rate and bandwidth<br>VBR/ABR/MBR H.264/H.265<br>Video streaming indicator   |
| <b>Image settings</b>                    | Saturation, contrast, brightness, sharpness, Forensic WDR: up to 120 dB depending on scene, white balance, day/night threshold, tone mapping, local contrast, EIS, exposure mode, exposure zones, defogging, compression, rotation: auto, 0°, 90°, 180°, 270° including Corridor Format, dynamic text and image overlays, polygon privacy mask, mirroring of images<br>Scene profiles: forensic, vivid, traffic overview |
| Audio                                    |  |
| <b>Audio encoding</b>                    | SDI: AES3 24 bit, 48 kHz<br>HDMI: LPCM 24 bit, 48 kHz<br>Network: AAC-LC 8/16/32/44.1/48 kHz, G.711 PCM 8 kHz, G.726 ADPCM 8 kHz, Opus 8/16/48 kHz, LPCM 48 kHz  |
| <b>Audio input/output</b>                | External microphone input or line input, ring power, network speaker pairing   |
| Network                                  |  |
| <b>Security</b>                          | Password protection, IP address filtering, HTTPS <sup>a</sup> encryption, IEEE 802.1x (EAP-TLS) <sup>a</sup> network access control, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware, secure boot, signed video, Axis Edge Vault, Axis device ID, secure keystore (CC EAL4 certified), TPM (FIPS 140-2 certified)                              |
| <b>Supported protocols</b>               | IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTPS <sup>a</sup> , HTTP/2, TLS <sup>a</sup> , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP <sup>®</sup> , SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, RTSP, RTP, SRTP, TCP, UDP, IGMPv1/v2/v3, RTCP, DHCPv4/v6, SOCKS, SSH, SIP, LLDP, CDP, MQTT v3.1.1, Syslog, Link-Local address (ZeroConf)  |
| System integration                       |  |
| <b>Application Programming Interface</b> | Open API for software integration, including VAPIX <sup>®</sup> and AXIS Camera Application Platform; specifications at <a href="http://axis.com">axis.com</a><br>One-click cloud connection<br>ONVIF <sup>®</sup> Profile G, ONVIF <sup>®</sup> Profile M, ONVIF <sup>®</sup> Profile S, and ONVIF <sup>®</sup> Profile T, specification at <a href="http://onvif.org">onvif.org</a>                                    |

|                                   | Support for Session Initiation Protocol (SIP) for integration with Voice over IP (VoIP) systems, peer to peer or integrated with SIP/PBX.   |
|-----------------------------------|---|
| <b>Event conditions</b>           | Audio: audio clip playing, audio detection<br>Device status: above operating temperature, above or below operating temperature, below operating temperature, IP address removed, network lost, new IP address, ring power overcurrent protection, storage failure, system ready, within operating temperature, shock detection<br>Digital audio: digital signal contains Axis metadata, digital signal has invalid sample rate, digital signal missing, digital signal OK<br>Edge storage: recording ongoing, storage disruption<br>I/O: digital input, manual trigger, virtual input<br>MQTT subscribe<br>PTZ: PTZ malfunctioning, PTZ movement, PTZ preset position reached, PTZ ready<br>Scheduled and recurring: scheduled event<br>Video: average bitrate degradation, day-night mode, live stream open, tampering |
| <b>Event actions</b>              | Record video: SD card and network share<br>MQTT publish<br>Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share and email<br>Pre- and post-alarm video or image buffering for recording or upload<br>Notification: email, HTTP, HTTPS, TCP and SNMP trap<br>PTZ: PTZ preset, start/stop guard tour<br>Overlay text, external output activation, play audio clip, zoom preset, day/night mode, make call   |
| <b>Data streaming</b>             | Event data  |
| <b>Built-in installation aids</b> | Leveling guide, pixel counter, license plate capture assistant  |
| Analytics                         |   |
| <b>AXIS Object Analytics</b>      | Object classes: humans, vehicles (types: cars, buses, trucks, bikes)<br>Trigger conditions: line crossing, object in area, time in area <sup>BETA</sup><br>Up to 10 scenarios<br>Metadata visualized with trajectories and color-coded bounding boxes<br>Polygon include/exclude areas<br>Perspective configuration<br>ONVIF Motion Alarm event   |
| <b>Applications</b>               | Included<br>AXIS Object Analytics<br>AXIS Video Motion Detection<br>Supported<br>AXIS Audio Spectrum Visualizer<br>Support for AXIS Camera Application Platform enabling installation of third-party applications, see <a href="http://axis.com/acap">axis.com/acap</a>   |
| General                           |   |
| <b>Casing</b>                     | Aluminum and plastic casing<br>Color: NCS S 9000-N  |
| <b>Sustainability</b>             | PVC free, BFR/CFR free  |
| <b>Power</b>                      | Power over Ethernet (PoE) IEEE 802.3at Type 2 Class 4<br>10–28 V DC, typical 12 W, max 13.5 W   |
| <b>Connectors</b>                 | Shielded RJ45 10BASE-T/100BASE-TX/1000BASE-T PoE<br>I/O: 6-pin 2.5 mm terminal block for four configurable inputs<br>RS485/RS422, 2 pcs, 2 pos, full duplex, terminal block<br>3.5 mm mic/line in, 3.5 mm line out<br>DC input<br>HDMI Type A, BNC for SDI<br>I2C for AXIS TQ1809–LE Housing  |
| <b>Storage</b>                    | Support for microSD/microSDHC/microSDXC card<br>Support for SD card encryption (AES-XTS-Plain64 256bit)<br>Recording to network-attached storage (NAS)<br>For SD card and NAS recommendations see <a href="http://axis.com">axis.com</a>  |
| <b>Operating conditions</b>       | –20 °C to 50 °C (–4 °F to 122 °F)<br>Humidity 10–85% RH (non-condensing)  |
| <b>Storage conditions</b>         | –40 °C to 65 °C (–40 °F to 149 °F)<br>Humidity 5–95% RH (non-condensing)  |

|                             |   |
|-----------------------------|---|
| <b>Approvals</b>            | <p>EMC<br/>EN 55035, EN 55032 Class A, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), KS C 9832 Class A, KS C 9835, RCM AS/NZS CISPR 32 Class A, VCCI Class A</p> <p>Safety<br/>CAN/CSA C22.2 No. 62368-1, IEC/EN/UL 62368-1, IS 13252</p> <p>Environment<br/>IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-78</p> <p>Network<br/>NIST SP500-267</p> |
| <b>Dimensions</b>           | Height: 66 x 80 x 195 mm (2.6 x 3.1 x 7.7 in)   |
| <b>Weight</b>               | 650 g (1.4 lb)  |
| <b>Included accessories</b> | Installation guide, Windows® decoder 1-user license, stand, connector kit, TORX® T20 screw driver, RESISTORX® L-key, terminal block connector   |

|                                  |   |
|----------------------------------|---|
| <b>Optional accessories</b>      | <p>AXIS TQ1809-LE Housing T92G<sup>b</sup><br/>AXIS T8415 Wireless Installation Tool<br/>AXIS Surveillance Cards<br/>For more accessories, see <a href="http://axis.com">axis.com</a></p> |
| <b>Video management software</b> | AXIS Companion, AXIS Camera Station, video management software from Axis Application Development Partners available at <a href="http://axis.com/vms">axis.com/vms</a>                     |
| <b>Languages</b>                 | English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Polish, Traditional Chinese   |
| <b>Warranty</b>                  | 5-year warranty, see <a href="http://axis.com/warranty">axis.com/warranty</a>   |

- a. *This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).*
- b. *The HDMI and SDI outputs are not available when the camera is mounted in the TQ1809-LE Housing.*

Environmental responsibility:

[axis.com/environmental-responsibility](http://axis.com/environmental-responsibility)