



ASSEMBLED IVAR FLOOR MIX UNDER-FLOOR MODULE (SOFT SEAL)

THIS PANEL IS TEMPERATURE CONTROLLED SYSTEM, WHERE THE THREE-WAY VALVE BLENDS WATER THROUGH THE RETURN MANIFOLD INTO THE FLOW MANIFOLD. THIS BLENDED SYSTEM IS USED WHEN YOU HAVE AN APPLIANCE THAT RUNS AT TEMPERATURES ABOVE 65 DEGREES. EG, GAS BOILER / DIESEL BOILER. ALSO SUITED TO A MULTIPLE MANIFOLD APPLICATIONS.

WITH OR WITHOUT CABINET, (INCLUDES) (INCLUDES)

MANIFOLD & MANIFOLD PIPE CONNECTOR & FLOOR MIX BLENDING MODULE

END SET WITH ISOLATING VALVE, 3/8" MANUAL AIR VENT, & DRAIN TAP

AUTO AIR VENT, PRESSURE GAUGE, TEMPERATURE GAUGE

25/6 B GRADE CAST CIRCULATING PUMP

BALL VALVES INCLUDED

CABINETS INCLUDED 750 HIGH, 140 DEEP X 600, 750, 900, 1050 & 1350 WIDE

NO ACTUATORS, WIRING CENTRES. SOLD SEPARATELY

ALL ELECTRICAL CONNECTIONS ARE DONE BY THE CLIENTS ELECTRICIAN.

ALL MODULES COME STANDARD LEFT HAND BOTTOM MAINS. PLEASE STATE YOUR MAINS PIPE OUT REQUIREMENTS WHEN ORDERING.

