



## tSec Reader

Sleek and stylish, and with a range of optional features, the tSec Reader series has a solution for everyone. Available in three sizes, multiple card capabilities, with an optional keypad, and in your choice of black or white, you can select the model to fit your needs and decor.

### Feature Highlights

- > Multi card technology provides support for DESFire, MIFARE, and 125kHz cards from a single reader
- > Encrypted RS-485 or standard Wiegand connection
- > Optional **Bluetooth®** / NFC credential reading
- > Configurable LED strip: 2 color control (blue and green) via external LED wiring, 16 color selectable for Protege function codes (RS-485 connection only)
- > Fully encapsulated design with environmental IP Rating of IP65 for outdoor and indoor operation
- > Read range up to 60mm (2.36") with proximity ISO cards
- > Three sizes suitable for any situation
- > Optional Vandal Resistant Cover

---

## Optional Features

A range of optional features means there is a model to suit everyone.

- > Available with or without capacitive touch keypad
- > Choose from the 125kHz or MIFARE/DESFire models, or the Multi Technology model that supports all formats
- > Optional Bluetooth® / NFC connectivity to allow access via a smartphone
- > Opt for either black or white according to your decor
- > Choose from three sizes to fit any situation

---

## Multi Card Technology

Available with 13.56MHz smart card capability or as a multi technology reader that combines both 125kHz proximity and 13.56MHz capabilities in a single unit, delivering maximum compatibility while providing a path forward to the latest technology. The multi technology reader is ideal for organizations that wish to transition to smart technology at their own pace, as it means they don't need to replace all their cards up front.

---

## Optional Bluetooth® / NFC Credential Reading

Bluetooth® / NFC capability enables you to use your smartphone as your access credential for maximum convenience. Equipped with support for most modern iOS and Android devices, you can unlock the door using a unique access credential that is entered against your user record in Protege, and authenticated by a secure cloud based server.

---

## Flexible Communication

Choose between the intelligent RS-485 connection for fast, flexible, secure communication, or Wiegand for compatibility with all standard access control systems. RS-485 provides the added benefits of being easier and more cost effective to wire and deploy, and allows for direct integration with Protege systems, enabling you to make changes on the fly once readers are installed. RS-485 also allows for longer cable runs and offers a simpler firmware update process.

---

## IP65 Protection

The IP65 environmental rating provides a high degree of protection from the elements, making the reader suitable for harsh environments. Readers can be mounted indoors or outdoors, located anywhere from the car park gate to the office door.

---

## Configurable LED Strip

The tSec Reader provides the ability to change the color of the LED strip (16 colors available) to show when a function has started, succeeded or failed. For example, when a function is used to arm an area you can set the LED to change to purple to show that the function has started, yellow to show that the area has armed successfully, and red to indicate that the function has failed.

\*This feature is only supported when wired using RS-485.

---

## Optional Vandal Resistant Cover

Designed to withstand some of the harshest settings, the optional vandal resistant covers are ideal for locations where a card reader may be exposed to damage, including corridors, parking buildings, correctional facilities, and other public places. Highly resistant to impact, such as from the swing of a hammer or baseball bat, its robust construction provides greater durability and protection against vandalism and malicious damage. The flush design also serves as an anti-ligature measure for an additional level of safety.



Covers can be ordered using the following part codes:

- > **tSec Standard Reader:** PRX-SVRC
- > **tSec Extra Reader:** PRX-XVRC
- > **tSec Mini Reader:** PRX-MVRC

Mounted correctly, the tSec Reader Vandal Resistant Cover is compliant to DHF TS 001:2013, the ENHANCED REQUIREMENTS & TEST METHODS FOR ANTI-LIGATURE HARDWARE to grade B4 for vertical direction devices and to impact level IK10".

### Keypad Support

Regular keypad variations of the tSec Reader range do not operate correctly with the vandal resistant covers that are provided separately. You must order the reader as a kit (including the cover) using one of the following part codes:

- > **tSec Standard Reader:** PRX-TSEC-STD-KP-VRC (Multi Technology), PRX-TSEC-STD-DF-KP-VRC (13.56MHz), PRX-TSEC-STD-KP-BT-B-VRC (Multi Technology with Bluetooth® Wireless Technology).
- > **tSec Extra Reader:** PRX-TSEC-EXTRA-KP-VRC (Multi Technology), PRX-TSEC-EXTRA-DF-KP-VRC (13.56MHz), PRX-TSEC-EXTRA-KP-BT-B-VRC (Multi Technology with Bluetooth® Wireless Technology).

## Reader Editions: tSec Standard Reader

The tSec Standard Reader is available in multiple editions, with a range of optional features:

tSec Standard Reader	115 x 45 x 18mm (4.53 x 1.77 x 0.71")				
	Keypad	125KHz	MIFARE/ DESFire/ NFC	Bluetooth® Technology	Vandal Resistant Cover*
PRX-TSEC-STD-B tSec Standard Multi-Technology Card Reader		✓	✓		
PRX-TSEC-STD-KP-B tSec Standard Multi-Technology Card Reader with Keypad	✓	✓	✓		
PRX-TSEC-STD-125-B tSec Standard 125KHz Card Reader		✓			
PRX-TSEC-STD-DF-B tSec Standard 13.56MHz Card Reader			✓		
PRX-TSEC-STD-DF-KP-B tSec Standard 13.56MHz Card Reader with Keypad	✓		✓		
PRX-TSEC-STD-BT-B PRX-TSEC-STD-BT-W tSec Standard Multi-Technology Card Reader with Bluetooth® Wireless Technology		✓	✓	✓	
PRX-TSEC-STD-KP-BT-B PRX-TSEC-STD-KP-BT-W tSec Standard Multi-Technology Card Reader with Keypad and Bluetooth® Wireless Technology	✓	✓	✓	✓	
PRX-TSEC-STD-KP-BT-B-VRC tSec Standard Multi-Technology Card Reader with Keypad, Vandal Resistant Cover and Bluetooth® Wireless Technology	✓	✓	✓	✓	✓
PRX-TSEC-STD-DF-BT-B tSec Standard 13.56MHz Card Reader with Bluetooth® Wireless Technology			✓	✓	
PRX-TSEC-STD-DF-KP-BT-B tSec Standard 13.56MHz Card Reader with Keypad and Bluetooth® Wireless Technology	✓		✓	✓	

\* Keypad editions with vandal resistant cover included. Covers may be purchased separately for readers without keypads, but regular keypad editions do not support vandal resistant covers.

## Reader Editions: tSec Extra Reader

The tSec Extra Reader is available in multiple editions, with a range of optional features:

tSec Extra Reader	115 x 73 x 18mm (4.53 x 2.87 x 0.71")				
	Keypad	125KHz	MIFARE/ DESFire/ NFC	Bluetooth® Technology	Vandal Resistant Cover*
PRX-TSEC-EXTRA-KP-B tSec Extra Multi-Technology Card Reader with Keypad	✓	✓	✓		
PRX-TSEC-EXTRA-125-B tSec Extra 125KHz Card Reader		✓			
PRX-TSEC-EXTRA-DF-B tSec Extra 13.56MHz Card Reader			✓		
PRX-TSEC-EXTRA-DF-KP-B tSec Extra 13.56MHz Card Reader with Keypad	✓		✓		
PRX-TSEC-EXTRA-BT-B PRX-TSEC-EXTRA-BT-W tSec Extra Multi-Technology Card Reader with Bluetooth® Wireless Technology		✓	✓	✓	
PRX-TSEC-EXTRA-KP-BT-B PRX-TSEC-EXTRA-KP-BT-W tSec Extra Multi-Technology Card Reader with Keypad and Bluetooth® Wireless Technology	✓	✓	✓	✓	
PRX-TSEC-EXTRA-KP-BT-B-VRC tSec Extra Multi-Technology Card Reader with Keypad, Vandal Resistant Cover and Bluetooth® Wireless Technology	✓	✓	✓	✓	✓
PRX-TSEC-EXTRA-DF-BT-B tSec Extra 13.56MHz Card Reader with Bluetooth® Wireless Technology			✓	✓	

\* Keypad editions with vandal resistant cover included. Covers may be purchased separately for readers without keypads, but regular keypad editions do not support vandal resistant covers.

## Reader Editions: tSec Mini Reader

The tSec Mini Reader is available in multiple editions, with a range of optional features:

tSec Mini Reader	84 x 45 x 17mm (3.31 x 1.77 x 0.67")				
	Keypad	125KHz	MIFARE/ DESFire/ NFC	Bluetooth® Technology	Vandal Resistant Cover*
PRX-TSEC-MINI-B tSec Mini Multi-Technology Card Reader		✓	✓		
PRX-TSEC-MINI-125-B tSec Mini 125KHz Card Reader		✓			
PRX-TSEC-MINI-DF-B tSec Mini 13.56MHz Card Reader			✓		
PRX-TSEC-MINI-BT-B PRX-TSEC-MINI-BT-W tSec Mini Multi-Technology Card Reader with Bluetooth® Wireless Technology		✓	✓	✓	
PRX-TSEC-MINI-DF-BT-B tSec Mini 13.56MHz Card Reader with Bluetooth® Wireless Technology			✓	✓	

\* Keypad editions with vandal resistant cover included. Covers may be purchased separately for readers without keypads, but regular keypad editions do not support vandal resistant covers.

## Technical Specifications

Ordering Information	
Order Codes	See tSec Reader editions.
Power Supply	
Operating Voltage	12VDC (9.5 to 14VDC)
Operating Current	tSec Standard Reader: 254mA (peak, reading) tSec Extra Reader: 298mA (peak, reading) tSec Mini Reader: 203mA (peak, reading)
Communications	
Card Read Range	MIFARE 60mm (2.36") * DESFire EV1 ISO 15mm (0.6") * 125kHz Clamshell 40mm (1.57") †
Tag Read Range	MIFARE 30mm (1.2") * DESFire EV1 6mm (0.23") * 125kHz 25mm (0.98") †
Wiegand Interface	Multiple format 26 or 34 Bit data 0 and data 1, card defined.
Frequency	13.56 MHz ISO/IEC 14443 Type A* 125KHz pulse width modulated†
Multi Conductor Cable	Wiegand: 22Awg alpha 5196, 5198, 18Awg alpha 5386, 5388. Max Distance 150m (492ft) Module comms/RS485: Belden 9842 or equivalent. Max distance 900m (3000ft)
Bluetooth® Wireless Technology	
Bluetooth® Read Range	Proximity mode: up to 0.5m (1.6ft) Configurable** Action unlock (shake): up to 5m (16.4ft) Configurable**
Bluetooth® Electronic Credential Transmission Technology	NRF8001 Bluetooth® version 4.0 compliant Proprietary data exchange protocol. AES128 Encrypted Reader App Version: 1.04.175 and above Credentials can be distinguished by unique site code and card number
Bluetooth® Wireless Device	Protege Mobile 1.0.x
NFC	
NFC Read Range	Up to 60mm***
NFC (Near-field communication) electronic credential transmission technology	Android 4.4 or above, with phones which support ISO7816-4 Proprietary Secured DESFire credential Credential is AES-256 (NIST certified AES algorithm) Reader App Version: 1.04.175 and above Credentials can be distinguished by unique site code and card number
NFC Wireless Device	Protege Mobile 1.0.x
Operating Conditions	
Environment IP Rating	IP65

Operating Temperature	UL/ULC -35° to 66°C (-31° to 151°F) : EU EN -40° to 70°C (-40° to 158°F)
Storage Temperature	-10° - 85 °C (14° - 185 °F)
Mean Time Between Failures (MTBF)	520,834 hours (calculated using RFD 2000 (UTE C 80-810) Standard)
<b>Dimensions</b>	
Reader Dimensions (H x W x D)	tSec Standard Reader: 115 x 45 x 18mm (4.53 x 1.77 x 0.71")
	tSec Extra Reader: 115 x 73 x 18mm (4.53 x 2.87 x 0.71")
	tSec Mini Reader: 84 x 45 x 17mm (3.31 x 1.77 x 0.67")
Weight	tSec Standard Reader: 110g (3.89oz)
	tSec Extra Reader: 155.8g (5.5oz)
	tSec Mini Reader: 80g (2.82oz)

\* Applies to the MIFARE/DESFire and Multi-Technology models only

† Applies to the 125kHz and Multi-Technology models only

\*\* Applies to the Bluetooth® wireless technology enabled models only

\*\*\* Applies to the NFC capable models only

The size of conductor used for the supply of power to the unit should be adequate to prevent voltage drop at the terminals of no more than 5% of the rated supply voltage.

The **Bluetooth®** word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by ICT is under license. Other trademarks and trade names are those of their respective owners.



---

## Regulatory Notices

### **New Zealand (RSM) and Australia (RCM)**

This equipment carries the R-NZ label and complies with EMC and radio communications regulations of the Australian Communications and Media Authority (ACMA) governing the Australian and New Zealand (AS/NZ) communities.

### **CE – Compliance with European Union (EU)**

Conforms where applicable to European Union (EU) Low Voltage Directive (LVD) 2014/35/EU, Electromagnetic Compatibility (EMC) Directive 2014/30/EU, Radio Equipment Directive (RED) 2014/53/EU and RoHS Recast (RoHS2) Directive: 2011/65/EU + Amendment Directive (EU) 2015/863.

This equipment complies with the rules, of the Official Journal of the European Union, for governing the Self Declaration of the CE Marking for the European Union as specified in the above directives.

Security Grade 4, Environmental Class II, EN 50131-1:2006+A2:2017, EN 50131-3:2009, EN 50131-6:2008+A1:2014, EN 50131-10:2014, EN 50136-1:2012, EN 50136-2:2013, EN 60839-11-1:2013, Readers Environmental Class: IVA, IK07.

### **Federal Communications Commission (FCC)**

FCC Rules and Regulations CFR 47, Part 15, Class A.

This equipment complies with the limits for a Class A digital device, pursuant to Part 15 of the FCC rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference; (2) This device must accept any interference received, including interference that may cause undesired operation.

### **Industry Canada**

ICES-003

This is a Class A digital device that meets all requirements of the Canadian Interference-Causing Equipment Regulations.

CAN ICES-3 (A)/NMB-3(A)

### **UL/ULC (Underwriters Laboratories)**

- > UL 294 for Access Control System Units
- > CAN/ULC S319 for Electronic Access Control Systems
- > For a full regulatory and approval list please visit the ICT website.

**New Zealand**

4 John Glenn Ave  
Rosedale  
Auckland 0632  
Email: sales@ict.co  
Toll free: (0800) 428 111  
Ph: +64 9 476 7124

**USA**

5265 S Rio Grande Street  
Suite 201  
Littleton, CO 80120  
Email: ussales@ict.co  
Toll free: (855) 428 911  
Ph: +1 720 442 0767

**Canada**

6201 Highway 7  
Unit 7  
Vaughan, Ontario, L4H 0K  
Email: cansales@ict.co  
Ph: +1 647 724 3428

**Australia**

Building 4  
39-43 Duerdin Street  
Notting Hill, VIC 3168  
Email: ausales@ict.co  
Ph: +61 426 145 907

**EMEA**

Email: emeasales@ict.co  
Ph: +44 1625 800078

Designers & manufacturers of integrated electronic access control, security and automation products.

Designed & manufactured by Integrated Control Technology Ltd.

Copyright © Integrated Control Technology Limited 2003-2020. All rights reserved.

**Disclaimer:** Whilst every effort has been made to ensure accuracy in the representation of this product, neither Integrated Control Technology Ltd nor its employees shall be liable under any circumstances to any party in respect of decisions or actions they may make as a result of using this information. In accordance with the ICT policy of enhanced development, design and specifications are subject to change without notice.